

ISO 20794-3:2020-02 (E)

Road vehicles - Clock extension peripheral interface (CXPI) - Part 3: Transport and network layer

Contents

Page

| | |
|--------------|---|
| Foreword | v |
| Introduction | vi |
| 1 | Scope 1 |
| 2 | Normative references 1 |
| 3 | Terms and definitions 1 |
| 4 | Symbols and abbreviated terms 2 |
| 4.1 | Symbols 2 |
| 4.2 | Abbreviated terms 2 |
| 5 | Conventions 3 |
| 6 | Overview of transport layer and network layer 3 |
| 6.1 | Properties 3 |
| 6.2 | Packet types 3 |
| 6.3 | Error detection and indication 3 |
| 7 | Service interface parameters (SIP) 3 |
| 7.1 | SIP — General 3 |
| 7.2 | SIP — Data type definitions 4 |
| 7.3 | SIP — TA, target address 4 |
| 7.4 | SIP — SA, source address 4 |
| 7.5 | SIP — Ptype, packet type 4 |
| 7.6 | SIP — ReqId, request identifier 4 |
| 7.7 | SIP — ReqTypeId, request type identifier 5 |
| 7.8 | SIP — PDU, protocol data unit 5 |
| 7.9 | SIP — Length, length of PDU 5 |
| 7.10 | SIP — NMInfo, network management information 5 |
| 7.11 | SIP — SCT, sequence count 5 |
| 7.12 | SIP — Result, result 6 |
| 8 | Transport layer (TL) 6 |
| 8.1 | SI — T_Data.req and T_Data.ind service interface 6 |
| 8.2 | SI — T_Data.req and T_Data.ind service interface parameter mapping 7 |
| 8.3 | TL — Service interface with T_Ptype parameter mapping 8 |
| 8.3.1 | TL — T_Data.req and T_Data.ind with T_Ptype = NormalCom (T_Length = NULL) 8 |
| 8.3.2 | TL — T_Data.req and T_Data.ind with T_Ptype = NormalCom (T_Length ≥ '0') 9 |
| 8.3.3 | TL — T_Data.req and T_Data.ind interface with T_Ptype = DiagNodeCfg 10 |
| 8.4 | TL — Internal operation 11 |
| 8.5 | TL — T_PDU 11 |
| 8.5.1 | TL — T_PDU definition 11 |
| 8.5.2 | TL — T_PCI definition 11 |
| 8.6 | TL — Function models 12 |
| 8.6.1 | TL — Transmission logic 12 |
| 8.6.2 | TL — Reception logic 13 |
| 8.7 | TL — Error detection 14 |
| 9 | Network layer (NL) 14 |
| 9.1 | SI — N_Data.req and N_Data.ind service interface 14 |
| 9.2 | SI — N_Data.req and N_Data.ind service interface parameter mapping 15 |
| 9.3 | NL — Service interface with N_Ptype parameter mapping 16 |

| | | |
|--------------------------|--|-----------|
| 9.3.1 | NL — N_Data.req and N_Data.ind with N_Ptype = NormalCom (N_Length = NULL)..... | 16 |
| 9.3.2 | TL — N_Data.req and N_Data.ind with N_Ptype = NormalCom (N_Length ≥ '0').. | 17 |
| 9.3.3 | NL — N_Data.req and N_Data.ind interface with N_Ptype = DiagNodeCfg..... | 18 |
| 9.4 | NL — Internal operation..... | 19 |
| 9.5 | NL — N_PDU..... | 19 |
| 9.5.1 | NL — N_PDU definition..... | 19 |
| 9.5.2 | NL — N_NAD definition..... | 19 |
| 9.6 | NL — Function models..... | 20 |
| 9.6.1 | NL — Transmission logic..... | 20 |
| 9.6.2 | NL — Reception logic..... | 20 |
| 9.7 | NL — Timing definition..... | 21 |
| 9.7.1 | NL — General..... | 21 |
| 9.7.2 | NL — Timing constraints..... | 21 |
| 9.7.3 | NL — Timing parameters..... | 22 |
| 9.8 | NL — Error detection..... | 22 |
| Bibliography..... | | 23 |