

ISO 20794-4:2020-02 (E)

Road vehicles - Clock extension peripheral interface (CXPI) - Part 4: Data link layer and physical layer

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
4.1	Symbols	2
4.2	Abbreviated terms	3
5	Conventions	4
6	Introduction to data link layer and physical layer	5
6.1	Frames	5
6.2	Frame collision avoidance	5
6.3	Error detection and indication	5
6.4	Clock transmission and detection	5
7	Service interface parameters (SIP)	5
7.1	SIP — General	5
7.2	SIP — Data type definitions	5
7.3	SIP — Ftype, frame type	6
7.4	SIP — ReqId, request identifier	6
7.5	SIP — ReqTypeId, request type identifier	6
7.6	SIP — PDU, protocol data unit	6
7.7	SIP — Length, length of PDU	7
7.8	SIP — ev_wakeup_ind, event wake-up indication (optional)	7
7.9	SIP — cmd_wakeup_req, command wake-up request	7
7.10	SIP — NMInfo, network management information	8
7.11	SIP — SCT, sequence count	8
7.12	SIP — Result, result	8
8	Data link layer (DLL)	8
8.1	SI — L_Data.req and L_Data.ind service interface	8
8.2	SI — L_Data.req and L_Data.ind service interface parameter mapping	9
8.3	DLL — Service interface with L_Ftype parameter mapping	10
8.3.1	DLL — L_Data.req and L_Data.ind with L_Ftype = NormalCom (L_Length = NULL)	10
8.3.2	DLL — L_Data.req and L_Data.ind with L_Ftype = NormalCom (L_Length ≥ 0016)	11
8.3.3	DLL — L_Data.req and L_Data.ind interface with L_Ftype = DiagNodeCfg	12
8.4	DLL — Frame fields	13
8.4.1	DLL — Frame field definition	13
8.4.2	DLL — Request type identifier and request identifier fields	14
8.4.3	DLL — L_FI (frame information) field	15
8.4.4	DLL — L_DATA (data field)	16
8.4.5	DLL — L_CRC field	17
8.5	DLL — Internal operation	19
8.6	DLL — Timing parameters	20
8.6.1	DLL — IBS timing handling	20
8.6.2	DLL — IFS timing handling	20

8.6.3	DLL — Beginning condition of frame	21
8.6.4	DLL — Start of frame	22
8.6.5	DLL — Frame transmission time	22
8.7	DLL — Completion of frame	23
8.7.1	DLL — General	23
8.7.2	DLL — Completing condition of L_PTYPE field	23
8.7.3	DLL — Completing condition of L_PID field	23
8.7.4	DLL — Completing condition of frame	24
8.8	DLL — Byte arbitration	24
8.9	DLL — Function models	24
8.9.1	DLL — Transmission logic	24
8.9.2	DLL — Reception logic	25
8.10	DLL — Error detection	26
8.10.1	DLL — General	26
8.10.2	DLL — Byte error (Err_DLL_Byte)	26
8.10.3	DLL — CRC error (Err_DLL_CRC)	27
8.10.4	DLL — Parity error (Err_DLL_Parity)	27
8.10.5	DLL — Data length code error (Err_DLL_DLC)	27
8.10.6	DLL — Data length code extension error (Err_DLL_DLCext)	27
8.10.7	DLL — Framing error (Err_DLL_Framing)	28
8.10.8	DLL — Exception handling for L_FI_DLC = '1111 ₂ ' detection	28
9	Physical layer (PHY)	28
9.1	PHY — Overview	28
9.2	PHY — Concept of waveform generation	29
9.3	PHY — Physical signalling (PS) requirements	30
9.3.1	PHY — PS general	30
9.3.2	PHY — PS physical interface configuration	31
9.3.3	PHY — PS bit rate	31
9.3.4	PHY — PS bit sample timing	31
9.3.5	PHY — PS encoding and decoding logic	32
9.3.6	PHY — PS clock generation	35
9.3.7	PHY — PS node clock synchronization and bit synchronization	36
9.3.8	PHY — PS detection of clock existence	36
9.3.9	PHY — PS bit-wise collision resolution	37
9.3.10	PHY — PS AC parameters	37
9.3.11	PHY — PS node transmission of wake-up pulse	38
9.4	PHY — Physical medium attachment (PMA) requirements	39
9.4.1	PHY — PMA general	39
9.4.2	PHY — PMA electrical parameters	40
9.4.3	PHY — PMA AC parameters	42
9.4.4	PHY — PMA wake-up pulse and dominant pulse filter time	50
9.5	PHY — Physical media dependent (PMD) sub-layer requirements	53
9.5.1	PHY — PMD entity requirements	53
9.5.2	PHY — PMD device interface requirements	53
9.6	PHY — Physical media (PM) sub-layer requirements	54
9.7	PHY — Control and event services	54
9.7.1	PHY — Control and event service interface	54
9.7.2	PHY — Wake-up request	55
9.7.3	PHY — Wake-up event	55
	Bibliography	56