

# ISO 14229-8:2020-02 (E)

## Road vehicles - Unified diagnostic services (UDS) - Part 8: UDS on Clock eXtension Peripheral Interface (UDS onCXPI)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Abbreviated terms .....	2
5	Conventions .....	2
6	SIP - Service interface parameters .....	2
6.1	SIP - General .....	2
6.2	SIP -- Data type definitions .....	2
6.3	SIP -- A_Mtype, message type .....	3
6.4	SIP -- A_TAtype, target address type .....	3
6.5	SIP -- A_TA, target address .....	3
6.6	SIP -- A_SA, source address .....	3
6.7	SIP -- A_Length, length of A_PDU .....	4
6.8	SIP -- A_Data, protocol data unit .....	4
6.9	SIP -- A_SCT, sequence count .....	4
6.10	SIP -- A_Result, result .....	4
6.11	SIP -- ev_wakeup_ind, event wake-up indication (optional) .....	4
6.12	SIP -- cmd_wakeup_req, command wake-up request .....	5
6.13	SIP -- NMInfo, network management information .....	5
7	APP - Application .....	5
7.1	APP - General .....	5
7.2	APP - Definition of diagnostic classes .....	6
7.2.1	APP - Overview .....	6
7.2.2	APP - Diagnostic class I .....	6
7.2.3	APP - Diagnostic class II .....	6
7.2.4	APP - Diagnostic class III .....	6
7.3	APP - CXPI master node requirements - Master node fault management, sensor reading, I/O control .....	7
7.4	APP - CXPI slave node requirements .....	7
7.4.1	APP - General .....	7
7.4.2	APP - Error indications .....	7
7.5	APP - CXPI measurement and control data diagnostics .....	7
7.5.1	APP - Master handling of slave failure status measurement and control data .....	7
7.5.2	APP - Slave node current failure status support .....	7
7.6	APP - Network management (optional) .....	8
7.7	APP - CXPI master node gateway application .....	8
7.7.1	APP - General .....	8
7.7.2	APP - CXPI master gateway number of subnets .....	8
7.7.3	APP - CXPI master gateway address routing table .....	8
7.7.4	APP - CXPI master gateway all nodes request message handling .....	9
7.7.5	APP - Round trip of all node addressing with functional NAD .....	9

7.7.6	APP - Round trip of all node addressing with node-specific NADs .....	10
8	AL - Application layer .....	11
8.1	AL - Client to CXPI slave node(s) communication .....	11
8.2	AL - Overview of UDSONCXPI services and applicability to diagnostic classes .....	11
8.3	AL - CommunicationControl (2816) service .....	12
8.4	AL - UDSONCXPI services .....	13
8.4.1	AL - Supported functions .....	13
8.4.2	AL - Master node receive buffer length .....	14
8.4.3	AL - Message length is exceeded .....	14
8.5	AL - Protocol .....	14
8.6	AL - Timing .....	14
8.6.1	AL - General .....	14
8.6.2	AL - Timing parameter values .....	14
8.6.3	AL - Server timing performance requirements .....	14
8.6.4	AL - SuppressPosRspMsgIndicationBit .....	15
8.7	AL - Response pending .....	15
8.8	AL - CXPI slave node configuration services .....	16
8.8.1	AL - CXPI node configuration .....	16
8.8.2	AL - Slave node model .....	16
8.8.3	AL - WriteDataByIdentifier - AssignNodeAddress .....	20
8.8.4	AL - WriteDataByIdentifier - NodeDataDump .....	22
8.8.5	AL - ReadDataByIdentifier - NodeProductIdentification .....	23
8.8.6	AL - ReadDataByIdentifier - NodeSerialNumberIdentification .....	24
8.8.7	AL - ReadDataByIdentifier - NodeConfigurationFileAvailability .....	25
8.8.8	AL - WriteDataByIdentifier - SaveConfiguration .....	27
8.8.9	AL - WriteDataByIdentifier - AssignFramelIdentifierRange .....	28
9	PL - Presentation layer .....	29
10	SL - Session layer .....	29
10.1	SL - General .....	29
10.2	SL - A_Data and T_Data service interface parameter mapping .....	29
11	TL - Transport layer .....	30
11.1	TL - Service primitive interface adaptation - General information .....	30
11.2	TL - CXPI transport layer interface adaptation .....	30
11.2.1	TL - Mapping of session layer to transport layer service primitives .....	30
11.2.2	TL - Mapping of T_Data service primitive interface parameters .....	30
12	NL - Network layer .....	31
12.1	NL - Service primitive interface adaptation .....	31
12.1.1	NL - General information .....	31
12.1.2	NL - CXPI network layer interface adaptation .....	31
12.2	NL - CXPI master node .....	32
12.2.1	NL - Network layer .....	32
12.2.2	NL - Dynamic NAD assignment .....	32
12.2.3	NL - NodeIdentificationNumber .....	32
12.3	NL - Master message routing .....	32
12.3.1	NL - General .....	32
12.3.2	NL - Diagnostic request message routing .....	33
12.3.3	NL - Diagnostic response message routing .....	33
12.3.4	NL - Master node transport protocol support .....	33
12.4	NL - CXPI slave node .....	33
12.4.1	NL - General .....	33
12.4.2	NL - Node configuration handling .....	33
12.4.3	NL - Slave node diagnostic class II .....	34
12.4.4	NL - Slave node diagnostic class II - Fixed node address .....	34
12.4.5	NL - Slave node diagnostic class II - Ignore NAD 7E16 as broadcast .....	34
12.4.6	NL - Slave diagnostic class III - Network layer .....	34
12.4.7	NL - Slave diagnostic class III - Fixed node address .....	34

12.4.8	NL - Slave diagnostic class III - Accept NAD 7E16 as broadcast .....	34
13	DLL - Data link layer .....	34
	Annex A (normative) DID parameter definitions .....	35
	Annex B (informative) Guideline for P2CAN_Client setting .....	36
	Bibliography .....	43