ISO 14229-8:2020-02 (E)

Road vehicles - Unified diag nostic services (UDS) - Part 8: UDS on Clock eXtension Peripheral Interface (UDS onCXPI)

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Abbreviated terms 2

5 Conventions 2

6 SIP - Service interface parameters 2
6.1 SIP - General 2
6.2 SIP -- Data type definitions 2
6.3 SIP -- A_Mtype, message type 3
6.4 SIP -- A_TAtype, target address type 3
6.5 SIP -- A_TA, target address 3
6.6 SIP -- A_SA, source address 3
6.7 SIP -- A_Length, length of A_PDU 4
6.8 SIP -- A_Data, protocol data unit 4
6.9 SIP -- A_SCT, sequence count 4
6.10 SIP -- A_Result, result 4
6.11 SIP -- ev_wakeup_ind, event wake-up indication (optional) 4
6.12 SIP -- cmd_wakeup_req, command wake-up request 5
6.13 SIP -- NMInfo, network management information 5

7 APP - Application 5
7.1 APP - General 5
7.2 APP - Definition of diagnostic classes 6
7.2.1 APP - Overview 6
7.2.2 APP - Diagnostic class I 6
7.2.3 APP - Diagnostic class II 6
7.2.4 APP - Diagnostic class III 6
7.3 APP - CXPI master node requirements - Master node fault management, sensor reading, I/O control 7
7.4 APP - CXPI slave node requirements 7
7.4.1 APP - General 7
7.4.2 APP - Error indications 7
7.5 APP - CXPI measurement and control data diagnostics 7
7.5.1 APP - Master handling of slave failure status measurement and control data 7
7.5.2 APP - Slave node current failure status support 7
7.6 APP - Network management (optional) 8
7.7 APP - CXPI master node gateway application 8
7.7.1 APP - General 8
7.7.2 APP - CXPI master gateway number of subnets 8
7.7.3 APP - CXPI master gateway address routing table 8
7.7.4 APP - CXPI master gateway all nodes request message handling 9
7.7.5 APP - Round trip of all node addressing with functional NAD 9

7.7.6 APP - Round trip of all node addressing with node-specific NADs 10

8 AL - Application layer 11
8.1 AL - Client to CXPI slave node(s) communication 11
8.2 AL - Overview of UDSonCXPI services and applicability to diagnostic classes 11
8.3 AL - CommunicationControl (2816) service 12
8.4 AL - UDSonCXPI services 13
8.4.1 AL - Supported functions 13
8.4.2 AL - Master node receive buffer length 14

8.4.3 AL - Message length is exceeded 14
8.5 AL - Protocol 14
8.6 AL - Timing 14
8.6.1 AL - General 14
8.6.2 AL - Timing parameter values 14
8.6.3 AL - Server timing performance requirements 14
8.6.4 AL - SuppressPosRspMsgIndicationBit 15
8.7 AL - Response pending 15
8.8 AL - CXPI slave node configuration services 16
8.8.1 AL - CXPI node configuration 16
8.8.2 AL - Slave node model 16
8.8.3 AL - WriteDataByIdentifier - AssignNodeAddress 20
8.8.4 AL - WriteDataByIdentifier - NodeDataDump 22
8.8.5 AL - ReadDataByIdentifier - NodeProductIdentification 23
8.8.6 AL - ReadDataByIdentifier - NodeSerialNumberIdentification 24
8.8.7 AL - ReadDataByIdentifier - NodeConfigurationFileAvailability 25
8.8.8 AL - WriteDataByIdentifier - SaveConfiguration 27
8.8.9 AL - WriteDataByIdentifier - AssignFrameIdentifierRange 28

9 PL - Presentation layer 29

10 SL - Session layer 29
10.1 SL - General 29
10.2 SL - A_Data and T_Data service interface parameter mapping 29

11 TL - Transport layer 30
11.1 TL - Service primitive interface adaptation - General information 30
11.2 TL - CXPI transport layer interface adaptation 30
11.2.1 TL - Mapping of session layer to transport layer service primitives 30
11.2.2 TL - Mapping of T_Data service primitive interface parameters 30

12 NL - Network layer 31
12.1 NL - Service primitive interface adaptation 31
12.1.1 NL - General information 31
12.1.2 NL - CXPI network layer interface adaptation 31
12.2 NL - CXPI master node 32
12.2.1 NL - Network layer 32
12.2.2 NL - Dynamic NAD assignment 32
12.2.3 NL - NodeIdentificationNumber 32
12.3 NL - Master message routing 32
12.3.1 NL - General 32
12.3.2 NL - Diagnostic request message routing 33
12.3.3 NL - Diagnostic response message routing 33
12.3.4 NL - Master node transport protocol support 33
12.4 NL - CXPI slave node 33
12.4.1 NL - General 33
12.4.2 NL - Node configuration handling 33
12.4.3 NL - Slave node diagnostic class II 34
12.4.4 NL - Slave node diagnostic class II - Fixed node address 34
12.4.5 NL - Slave node diagnostic class II - Ignore NAD 7E16 as broadcast 34
12.4.6 NL - Slave diagnostic class III - Network layer 34
12.4.7 NL - Slave diagnostic class III - Fixed node address 34

12.4.8 NL - Slave diagnostic class III - Accept NAD 7E16 as broadcast 34

13 DLL - Data link layer 34

Annex A (normative) DID parameter definitions 35

Annex B (informative) Guideline for P2CAN_Client setting 36

Bibliography 43