

# ISO 22738:2020 (E)

## Intelligent transport systems — Localized communications — Optical camera communication

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	IEEE 802.15.7
5.1	General requirements
5.2	OCC PHY and MAC architecture
5.3	PHY mode
5.4	Modulation schemes
5.5	MAC frame format
5.6	Dimming
5.7	Mitigation of flickering
6	ITS station
6.1	ITS station and communication architecture
6.2	ITS-S service access points
6.2.1	General
6.2.2	Communications SAPs
6.2.3	Management SAPs
6.2.4	Security SAPs
6.3	Hybrid communications support
7	Communication interface protocol stack
7.1	Communication interface parameters
7.2	Physical layer
7.3	Data link layer
7.3.1	General
7.3.2	Communication adaptation sub-layer
8	Communication interface management
8.1	General management
8.2	Management adaptation entity
8.2.1	OCC parameters and I-Parameters
8.2.2	OCC management commands and MI-SAP commands and requests
9	Procedures
9.1	Transmit procedure
9.2	Receive procedures
9.3	Management procedures
10	Conformance
11	Test methods
Annex A	(normative) Communication interface parameters

<b>A.1</b>	<b>General</b>
<b>A.2</b>	<b>I-Parameters specific to ITS-OCC</b>
<b>A.3</b>	<b>Default of I-Parameters</b>
<b>Annex B</b>	<b>(normative) MI-COMMANDs</b>
<b>B.1</b>	<b>General</b>
<b>B.2</b>	<b>Required functionality</b>
<b>Annex C</b>	<b>(normative) MI-REQUESTs</b>
<b>C.1</b>	<b>General</b>
<b>C.2</b>	<b>Required functionality</b>
<b>Annex D</b>	<b>(normative) ASN.1 definitions</b>
<b>D.1</b>	<b>Overview</b>
<b>D.2</b>	<b>Module ITSocC</b>
<b>D.3</b>	<b>Definitions to be added in ISO 21218</b>
<b>D.4</b>	<b>Definitions to be added to the C-ITS Registry</b>
<b>Annex E</b>	<b>(informative) Frequency band and frequency allocation</b>
<b>E.1</b>	<b>Frequency band</b>
<b>E.2</b>	<b>Frequency allocation</b>
<b>Annex F</b>	<b>(informative) Dimming method</b>
<b>F.1</b>	<b>Overview</b>
<b>F.2</b>	<b>Dimming method</b>
<b>F.2.1</b>	<b>Dimming by controlling pulse width</b>
<b>F.2.2</b>	<b>Dimming by controlling pulse amplitude</b>
<b>F.2.3</b>	<b>Dimming by controlling brightness in out-of-band frequency</b>

Page count: 25