

ISO/TS 21176:2020 (E)

Cooperative intelligent transport systems (C-ITS) — Position, velocity and time functionality in the ITS station

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Abbreviated terms
5	Conformance
6	PVT service in the ITS station and communication architecture
6.1	ITS station and communication architecture
6.2	ITS-S application processes (ITS-S-APs)
6.3	ITS-S facilities layer services
6.4	PVT service provided by the ITS-S facilities layer
6.5	Access to the PVT service
6.6	PVT-augmented ADUs
7	PVT service
7.1	PVT service reference model
7.2	PVT-related input parameters
7.3	PVT output parameters
7.3.1	General
7.3.2	PvtInfoEcdd
7.3.3	PvtInfoEcdd-PosVelocityTime
7.3.4	PvtInfoEcdd-PosTime
7.3.5	PvtInfoEcdd-VelocityAccelerationTime
7.3.6	PvtInfoEcdd-VelocityTime
7.3.7	PvtInfoEcdd-SpeedTime
7.3.8	PvtInfoNmeaData
8	PVT-SAP service primitives
8.1	General
8.1.1	Overview
8.1.2	PVTinit
8.1.3	Return codes
8.2	Get-PVT
8.3	Subscribe-PVT-related service primitives
8.3.1	Subscribe-PVT
8.3.2	Notify-PVT
8.3.3	Cancel-PVT
9	PVT capability
Annex A	(normative) PVT data type specifications
Annex B	(normative) Implementation conformance statement proforma
B.1	Guidance for completing the ICS proforma
B.1.1	Purpose and structure

B.1.2	Abbreviations and conventions
B.2	Instruction for completing the ICS proforma
B.2.1	General
B.3	Global statement of conformance
B.4	ICS proforma tables

Page count: 28