

# ISO 21806-4:2020 (E)

## Road vehicles — Media Oriented Systems Transport (MOST) — Part 4: Transport layer and network layer

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Conventions
6	Transport layer service interface to upper OSI layers
6.1	Overview of services
6.2	Data type definitions
6.3	Parameters
6.3.1	Parameters — NL/TL to upper layers
6.3.1.1	Overview
6.3.1.2	Application_Event
6.3.1.3	NetInterface_Transition
6.3.1.4	DiagResult
6.3.1.5	Relative_Position
6.3.1.6	Shutdown_Reason
6.3.1.7	Node_Position
6.3.1.8	Maximum_Position
6.3.1.9	Transmission_Status
6.3.2	Parameters — Upper layers to TL/NL
6.3.2.1	Overview
6.3.2.2	Application_Request
6.3.2.3	Network_Startup_Type
6.3.2.4	Number_Of_Retries
6.3.2.5	Priority
6.3.2.6	Group_Address
6.3.2.7	Node_Address
6.3.2.8	EUI_48
6.3.2.9	Bandwidth
6.3.3	Parameters – NL/TL to upper layers and upper layers to TL/NL
6.3.3.1	Overview
6.3.3.2	Media_Interface_ID
6.3.3.3	Length
6.3.3.4	Data
6.3.3.5	MsgID
6.3.3.6	Session_ID
6.3.3.7	Target_Address
6.3.3.8	Source_Address
6.3.3.9	Destination_MAC_Address
6.3.3.10	Source_MAC_Address
6.4	Event indications and action requests
6.4.1	N_EVENT.INDICATE

- 6.4.2 N\_NODE\_POSITION.INDICATE
  - 6.4.3 N\_MAXIMUM\_NODE\_POSITION.INDICATE
  - 6.4.4 N\_NET\_INTERFACE\_TRANSITION.INDICATE
  - 6.4.5 N\_DIAGRESULT.INDICATE
  - 6.4.6 N\_SHUTDOWN\_REASON.INDICATE
  - 6.4.7 N\_ACTION.REQUEST
  - 6.4.8 N\_NETWORK\_STARTUP.REQUEST
  - 6.4.9 N\_SET\_GROUP\_ADDRESS.REQUEST
  - 6.4.10 N\_SET\_NODE\_ADDRESS.REQUEST
  - 6.4.11 N\_SET\_EUI\_48.REQUEST
  - 6.5 Control data
    - 6.5.1 N\_CONTROL\_DATA.RECEIVE
    - 6.5.2 N\_CONTROL\_DATA.CONFIRM
    - 6.5.3 N\_SET\_MESSAGE\_ATTRIBUTES.REQUEST
    - 6.5.4 N\_CONTROL\_DATA.SEND
  - 6.6 Packet data
    - 6.6.1 16-bit addressing
      - 6.6.1.1 N\_PACKET\_DATA\_16.RECEIVE
      - 6.6.1.2 N\_PACKET\_DATA\_16.SEND
    - 6.6.2 48-bit addressing
      - 6.6.2.1 N\_PACKET\_DATA\_48.RECEIVE
      - 6.6.2.2 N\_PACKET\_DATA\_48.SEND
  - 6.7 Streaming data
    - 6.7.1 N\_ALLOCATE.INDICATE
    - 6.7.2 N\_DEALLOCATE.INDICATE
    - 6.7.3 N\_CONNECT.INDICATE
    - 6.7.4 N\_DISCONNECT.INDICATE
    - 6.7.5 N\_SOURCE\_DROP.INDICATE
    - 6.7.6 N\_STREAMING\_DATA.RECEIVE
    - 6.7.7 N\_ALLOCATE.REQUEST
    - 6.7.8 N\_DEALLOCATE.REQUEST
    - 6.7.9 N\_CONNECT.REQUEST
    - 6.7.10 N\_DISCONNECT.REQUEST
    - 6.7.11 N\_STREAMING\_DATA.SEND
  - 7 TL — Transport layer
    - 7.1 TL — Overview
    - 7.2 TL — Data transport mechanism
      - 7.2.1 TL — Transport service
        - 7.2.2 TL — Service for control data
          - 7.2.2.1 TL — Application message service (AMS)
          - 7.2.2.2 TL — Message identifier (MsgID)
          - 7.2.2.3 TL — Control data
            - 7.2.2.4 TL — Telegram identifier (TelID)
            - 7.2.2.5 TL — Telegram length (TelLen)
            - 7.2.2.6 TL — Payload
              - 7.2.2.7 TL — Single transfer
              - 7.2.2.8 TL — Segmented transfer
                - 7.2.2.8.1 TL — Size-prefix for segmented transfer
                  - 7.2.2.8.1.1 TL — Purpose
                  - 7.2.2.8.1.2 TL — Message size
                    - 7.2.2.8.2 TL — Transfer of payload
      - 7.2.3 TL — Service for source data
        - 7.2.3.1 TL — General
        - 7.2.3.2 TL — Packet data
        - 7.2.3.3 TL — Streaming data
- 8 NL — Network layer
  - 8.1 NL — Overview
  - 8.2 NL — Services
    - 8.2.1 NL — States and state transitions
      - 8.2.1.1 NL — Overview
      - 8.2.1.2 NL — Dynamic behaviour of a node
      - 8.2.1.3 NL — NetInterface states

- 8.2.1.3.1 NL — Overview
- 8.2.1.3.2 NL — NetInterface state s\_NetInterface\_Sleep
- 8.2.1.3.3 NL — NetInterface state s\_NetInterface\_Off
- 8.2.1.3.4 NL — NetInterface state s\_NetInterface\_Init
- 8.2.1.3.5 NL — NetInterface state s\_NetInterface\_Normal\_Operation
- 8.2.1.3.6 NL — NetInterface state s\_NetInterface\_Diagnosis
- 8.2.1.4 NL — Network wake-up and startup
- 8.2.1.5 NL — Network shutdown
- 8.2.2 NL — Network error detection and management
- 8.2.2.1 NL — Network failure
- 8.2.2.2 NL — Unlock
- 8.2.2.3 NL — Handling sudden signal off and critical unlock
- 8.2.2.4 NL — Undervoltage management
- 8.2.2.5 NL — General
- 8.2.2.6 NL — Active voltage UActive
- 8.2.2.7 NL — Sleep voltage USleep
- 8.3 NL — Timing
- 8.3.1 NL — General
- 8.3.2 NL — Timers
- 8.3.3 NL — Timing constraints
- 8.3.4 NL — Network startup and changes
- 8.3.4.1 NL — General
- 8.3.4.2 NL — Constraint tWakeUp
- 8.3.4.2.1 NL — General
- 8.3.4.2.2 NL — Validity conditions
- 8.3.4.2.3 NL — Violation consequences
- 8.3.4.3 NL — Constraint tWaitNodes
- 8.3.4.3.1 NL — General
- 8.3.4.3.2 NL — Validity conditions
- 8.3.4.3.3 NL — Violation consequences
- 8.3.4.4 NL — Constraint tLock
- 8.3.4.4.1 NL — General
- 8.3.4.4.2 NL — Validity conditions
- 8.3.4.4.3 NL — Violation consequences
- 8.3.4.5 NL — Timer tConfig
- 8.3.4.5.1 NL — General
- 8.3.4.5.2 NL — Start and stop conditions
- 8.3.4.5.3 NL — Timer expiration
- 8.3.4.6 NL — Timer tRestart
- 8.3.4.6.1 NL — General
- 8.3.4.6.2 NL — Start and stop conditions
- 8.3.4.6.3 NL — Timer expiration
- 8.3.5 NL — Network shutdown
- 8.3.5.1 NL — General
- 8.3.5.2 NL — Constraint tShutdown
- 8.3.5.2.1 NL — General
- 8.3.5.2.2 NL — Validity conditions
- 8.3.5.2.3 NL — Violation consequences
- 8.3.5.3 NL — Timer tSSO\_Shutdown
- 8.3.5.3.1 NL — General
- 8.3.5.3.2 NL — Start and stop conditions
- 8.3.5.3.3 NL — General
- 8.3.5.3.4 NL — Timer expiration
- 8.3.5.4 NL — Timer tUnlock
- 8.3.5.4.1 NL — General
- 8.3.5.4.2 NL — Start and stop conditions
- 8.3.5.4.3 NL — Timer expiration
- 8.3.5.5 NL — Timer tPwrSwitchOffDelay
- 8.3.5.5.1 NL — General
- 8.3.5.5.2 NL — Start and stop conditions
- 8.3.5.5.3 NL — Timer expiration
- 8.3.6 NL — General communication
- 8.3.6.1 NL — General
- 8.3.6.2 NL — Timer tWaitForNextSegment

- 8.3.6.2.1 NL — Purpose
- 8.3.6.2.2 NL — Start and Stop conditions
- 8.3.6.2.3 NL — Timer expiration
- 8.4 NL — Data link layer service interface

**Annex A (informative) Ring break diagnosis (RBD)**

- A.1 General
- A.2 Functional description
- A.3 TimingSlave behaviour
- A.4 TimingMaster behaviour
- A.5 Ring break diagnosis result
- A.6 Alternative behaviour
- A.7 Timing
  - A.7.1 General
  - A.7.2 Timers
  - A.7.3 Timing constraints
  - A.7.4 RBD timers and timing constraint

Page count: 56