

ISO 20794-5:2020 (E)

Road vehicles — Clock extension peripheral interface (CXPI) — Part 5: Application layer conformance test plan

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Conventions
6	General test specification considerations
6.1	General
6.2	Test conditions
6.3	IUT requirements
6.4	CTC definition
6.5	Test system set-up
6.6	Configuration of test system and IUT
6.6.1	General
6.6.2	IUT-specific set-up parameters
6.6.3	User_Specific configurations
6.6.4	W/S_Init configurations
6.6.5	W/S_Passive configurations
6.6.6	W/S_RdySleep configurations
6.6.7	W/S_NotRdySleep configurations
6.6.8	A_WSSup configurations
6.6.9	NonW/S configurations
6.6.10	ErrDet configurations
6.6.11	Event configurations
6.6.12	Polling configurations
6.7	SUT initialisation
6.7.1	General
6.7.2	Default initialisation
6.7.3	Sleep initialisation
6.7.4	Power-off initialisation
6.7.5	Transmission prohibition initialisation
6.7.6	Clock supply of secondary clock master initialisation
7	Application conformance test plan
7.1	General
7.2	Network management
7.2.1	General
7.2.2	State transition definition
7.2.3	State transition CTCs
7.2.3.1	8.CTC_1.1 – State machine – Master node – Wake-up/Sleep supported
7.2.3.2	8.CTC_1.2 – State machine – Master node – Wake-up/Sleep not supported
7.2.3.3	8.CTC_1.3 – State machine – Slave node – Wake-up/Sleep supported
7.2.3.4	8.CTC_1.4 – State machine – Slave node – Sleep permission

7.2.3.5	8.CTC_1.5 – State machine – Slave node – Sleep prohibition
7.2.3.6	8.CTC_1.6 – State machine – Slave node – Transition into the normal state
7.2.4	Wake-up request/notification of master node trigger CTCs
7.2.4.1	8.CTC_2.1 – Master node wake-up sequence – Master node trigger
7.2.4.2	8.CTC_2.2 – Slave node wake-up sequence – Master node trigger
7.2.4.3	8.CTC_2.3 – Master node wakeup_ind value verification, master node trigger
7.2.4.4	8.CTC_2.4 – Slave node wakeup_ind value verification, master node trigger
7.2.5	Wake-up request/notification of slave node trigger CTCs
7.2.5.1	8.CTC_3.1 – Slave node wake-up request – Slave node trigger
7.2.5.2	8.CTC_3.2 – Slave node wake-up pulse retransmission sequence – Slave node trigger
7.2.5.3	8.CTC_3.3 – Slave node wake-up notification – Slave node trigger
7.2.5.4	8.CTC_3.4 – Master node wake-up sequence – Slave node trigger
7.2.5.5	8.CTC_3.5 – Slave node wake-up sequence – Dominant pulse
7.2.5.6	8.CTC_3.6 – Master node wakeup_ind value verification, slave node trigger
7.2.5.7	8.CTC_3.7 – Slave node wakeup_ind value verification, slave node trigger
7.2.5.8	8.CTC_3.8 – Slave node wakeup_ind value verification upon wake-up pulse transmission
7.2.6	Sleep request/notification CTCs
7.2.6.1	8.CTC_4.1 – Master node sleep_ind verification
7.2.6.2	8.CTC_4.2 – Slave node sleep_ind verification
7.2.6.3	8.CTC_4.3 – Sleep message reception
7.2.6.4	8.CTC_4.4 – Sleep message transmission
7.2.6.5	8.CTC_4.5 – Abort sleep message transmission by losing arbitration 1
7.2.6.6	8.CTC_4.6 – Abort sleep message transmission by losing arbitration 2
7.2.6.7	8.CTC_4.7 – Abort sleep message transmission by transmission error
7.2.7	Network Management multi clock master processing CTCs
7.2.7.1	8.CTC_5.1 – Multi clock master sequence – Wake-up/Sleep supported
7.2.7.2	8.CTC_5.2 – Multi clock master sequence – Wake-up/Sleep not supported
7.2.7.3	8.CTC_5.3 – Clock supply stop of secondary clock master 1
7.2.7.4	8.CTC_5.4 – Clock supply stop of secondary clock master 2
7.3	Fault management
7.3.1	Error detection/recovery CTCs
7.3.1.1	8.CTC_6.1 – Transmission prohibition 1 as master
7.3.1.2	8.CTC_6.2 – Transmission prohibition 1 as slave
7.3.1.3	8.CTC_6.3 – Transmission prohibition 2 as master
7.3.1.4	8.CTC_6.4 – Transmission prohibition 2 as slave
7.3.1.5	8.CTC_6.5 – Master node recovery from transmission prohibition by system reset
7.3.1.6	8.CTC_6.6 – Master node recovery from transmission prohibition by sleep/wake-up
7.3.1.7	8.CTC_6.7 – Slave node recovery from transmission prohibition by sleep/wake-up
7.3.1.8	8.CTC_6.8 – Slave node recovery from transmission prohibition by system reset
7.3.1.9	8.CTC_6.9 – Recovery from transmission prohibition by normal reception
7.3.2	CXPI network error CTCs
7.3.2.1	8.CTC_7.1 – CXPI network error handling – Wake-up/Sleep supported
7.3.2.2	8.CTC_7.2 – CXPI network error handling
7.3.3	SCT error CTCs
7.3.3.1	8.CTC_8.1 – Outbreak of the count error and recovery from SCT error
7.3.4	Error notification between CXPI nodes CTCs
7.3.4.1	8.CTC_9.1 – Supported error types for error notification between CXPI nodes

8 Application layer conformance test plan

8.1	General
8.2	Transfer management CTCs
8.2.1	General
8.2.2	7.CTC_10.1 – Master node event-triggered method
8.2.3	7.CTC_10.2 – Slave node event-triggered method
8.2.4	7.CTC_10.3 – Master node polling method
8.2.5	7.CTC_10.4 – Slave node polling method
8.2.6	7.CTC_10.5 – Behaviour of unknown or invalid ReqId reception
8.2.7	7.CTC_10.6 – Master node sets unused bits in response message
8.2.8	7.CTC_10.7 – Slave node sets unused bits in response message