

ISO 20730-1:2021 (E)

Road vehicles — Vehicle interface for electronic Periodic Technical Inspection (ePTI) — Part 1: Application and communication requirements

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	How to read this document
5.1	Layout of the document
5.2	Use case structure explanation
5.3	Requirements statement structure
5.4	ePTI application example
6	ePTI inspection modules and use cases overview and principles
6.1	Basic principles
6.2	ePTI inspection modules
7	IM-1 – Discover ePTI data link and ePTI-relevant system(s)
7.1	UC 1.1 – Discover ePTI data link
7.2	UC 1.2 – Discover ePTI-relevant system(s)
8	IM-2 – Authentication, authorisation
8.1	UC 2.1 – ePTI external test equipment authentication
8.2	UC 2.2 – Vehicle ECU authentication
9	IM-3 – Query available ePTI identifier(s)
9.1	UC 3.1 – Query supported data identifier(s)
9.2	UC 3.2 – Query supported routine identifier(s)
9.3	UC 3.3 – Query supported input/output control identifier(s)
10	IM-4 – Query ePTI system information
10.1	UC 4.1 – Query vehicle identification number
10.2	UC 4.2 – Query vehicle odometer value
10.3	UC 4.3 – Query system's software number
10.4	UC 4.4 – Identify installed system's software integrity information
10.5	UC 4.5 – Query information from system
11	IM-5 – Query system's self-test completion and error information
11.1	UC 5.1 – Query system's self-test completion status
11.2	UC 5.2 – Query system status and error information
12	IM-6 – Activate system's routines, input/output control(s)
12.1	UC 6.1 – Activate system's routine(s)
12.2	UC 6.2 – Activate system's input/output control(s)
13	Overview of vehicle system requirements
13.1	ePTI external test equipment and vehicle message exchange sequence
13.2	Technical requirements and use case coverage

- 14 **Application (APP)**
 - 14.1 Setup vehicle's DoCAN data link framework
 - 14.2 Setup vehicle's DoIP data link framework
 - 14.3 Choice of DoCAN and DoIP data link in the vehicle
- 15 **Application layer (AL)**
 - 15.1 Applicable ISO 14229-1 UDS functionality
 - 15.2 Authentication
 - 15.2.1 Requirements definition — ePTI external test equipment authentication
 - 15.2.2 Requirements definition — ECU authentication
 - 15.3 ReadDataByIdentifier — Report ePTI-relevant system(s)
 - 15.3.1 Requirements definition — Report ePTI-relevant system(s)
 - 15.3.2 Message sequence implementation requirements — Report ePTI-relevant system(s)
 - 15.3.3 Example of the message sequence — Report ePTI-relevant system(s)
 - 15.4 ReadDataByIdentifier — Report ECU supported data identifier(s)
 - 15.4.1 Requirements definition — Report ECU supported data identifier(s)
 - 15.4.2 Message sequence implementation requirements — Report ECU supported data identifier(s)
 - 15.4.3 Example of the message sequence — Report ECU supported data identifier(s)
 - 15.5 ReadDataByIdentifier — Report ECU supported routine identifier(s)
 - 15.5.1 Requirements definition — Report ECU supported routine identifier(s)
 - 15.5.2 Message sequence implementation requirements — Report ECU supported routine identifier(s)
 - 15.5.3 Example of the message sequence — Report ECU supported routine identifier(s)
 - 15.6 ReadDataByIdentifier — Report ECU supported input/output control identifier(s)
 - 15.6.1 Requirements definition — Report ECU supported input/output control identifier(s)
 - 15.6.2 Message sequence implementation requirements — Report ECU supported input/output control identifier(s)
 - 15.6.3 Example of the message sequence — Report ECU supported input/output control identifier(s)
 - 15.7 ReadDataByIdentifier — Report VIN from ECU
 - 15.7.1 Requirements definition — Report VIN from ECU
 - 15.7.2 Message sequence implementation requirements — Report VIN from ECU
 - 15.7.3 Example of the message sequence — Report VIN from ECU
 - 15.8 ReadDataByIdentifier — Report vehicle odometer value
 - 15.8.1 Requirements definition — Report vehicle odometer value
 - 15.8.2 Message sequence implementation requirements — Report vehicle odometer value
 - 15.8.3 Example of the message sequence — Report vehicle odometer value
 - 15.9 ReadDataByIdentifier — Report vehicle's system software number(s)
 - 15.9.1 Requirements definition — Report vehicle's system software number(s)
 - 15.9.2 Message sequence implementation requirements — Report vehicle's system software number(s)
 - 15.10 ReadDataByIdentifier — Report information from system
 - 15.10.1 Requirements definition — Report information from system
 - 15.10.2 Message sequence implementation requirements — Report information from system
 - 15.10.3 Example of the message sequence — Report information from system
 - 15.11 ReadDataByIdentifier — Report vehicle's ePTI system self-test completion and system status
 - 15.11.1 Requirements definition — Report vehicle's ePTI system self-test completion and system status
 - 15.11.2 Message sequence implementation requirements — Report vehicle's ePTI system self-test completion and system status
 - 15.11.3 Example of the message sequence — Report vehicle's ePTI system self-test completion and system status
 - 15.12 RoutineControl — Activate system's routines
 - 15.12.1 Requirements definition — Activate system's routines
 - 15.12.2 Message sequence implementation requirements — Activate system's routines
 - 15.12.3 Example of the message sequence — Activate system's routines exterior lights
 - 15.13 InputOutputControlByIdentifier — Activate system's input/output controls
 - 15.13.1 Requirements definition — Activate system's input/output controls
 - 15.13.2 Message sequence implementation requirements — Activate system's input/output controls
 - 15.13.3 Example of the message sequence — Activate system's input/output controls
- 16 **Session layer (SL)**