ISO 22737:2021 (E)

Intelligent transport systems — Low-speed automated driving (LSAD) systems for predefined routes — Performance requirements, system requirements and performance test procedures

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

5 Example use case for an LSAD system deployment

6 LSAD system architecture

7 Basic requirements

7.1 General
7.2 Minimum operating capabilities
7.3 Operational design domains (ODDs)
7.4 LSAD state transition diagram
7.4.1 LSAD state functional descriptions
7.4.1.1 LSAD off
7.4.1.2 LSAD standby
7.4.1.3 LSAD active
7.4.2 LSAD state transition description:
7.4.2.1 A1
7.4.2.2 B1
7.4.2.3 B2
7.4.2.4 C1
7.4.2.5 C2
7.4.2.6 C3
7.4.2.7 C4
7.4.2.8 C5
7.4.2.9 C6
7.4.3 Possible extension of the LSAD state diagram to accommodate dispatcher inputs
7.4.3.1 Safe to proceed confirmation request
7.4.3.2 Safe to proceed confirmation authorization
7.4.3.3 Operating mode command
7.5 Communication requirements

8 Functional requirements

8.1 Determination of hazardous situation
8.1.1 General
8.1.2 Non-occluded view
8.1.3 Occluded view
8.2 Minimal risk manoeuvre (MRM)
8.3 Driving in the drivable area
8.4 Emergency stop (e-stop)

9 Performance requirements for the LSAD system

9.1 Maximum subject vehicle speed (VSV_max)

9.2 Obstacle detection requirements
9.2.1 Maximum pedestrian speed (Vped_max)
9.2.2 Maximum pedal cyclist speed (Vpc_max)
9.2.3 LSAD system deceleration

10 System requirements

10.1 Recording data about a safety-critical event

11 Performance test procedures

11.1 General
11.2 Environmental parameters
11.3 Hazardous situation
11.3.1 Pedestrian as an obstacle
11.3.1.1 Test setup
11.3.1.2 Vehicle parameters
11.3.1.3 Pedestrian target parameters – Situation A
11.3.1.4 Pedestrian and vehicle target parameters – Situation B
11.3.1.5 Pedestrian target parameters – Situation C
11.3.1.6 Longitudinal start distance
11.3.1.7 Environmental parameters
11.3.1.8 Pass criteria
11.3.2 Pedal cyclist as an obstacle
11.3.2.1 Test setup
11.3.2.2 Vehicle parameters
11.3.2.3 Pedal cyclist target parameters – Situation A
11.3.2.4 Pedal cyclist and Vehicle Target Parameters – Situation B
11.3.2.5 Pedal cyclist target parameters – Situation C
11.3.2.6 Longitudinal start distance, Slong
11.3.2.7 Environmental parameters
11.3.2.8 Pass criteria
11.3.3 Hazardous situation turning around a corner
11.3.3.1 Test setup
11.3.3.2 Vehicle parameters
11.3.3.3 Pedestrian target parameters
11.3.3.4 Longitudinal start distance (Slong)
11.3.3.5 Lateral detection evaluation zone (Slat1)
11.3.3.6 Environmental parameters
11.3.3.7 Pass criteria
11.3.4 False positive tests
11.3.4.1 Test setup
11.3.4.2 Vehicle parameters
11.3.4.3 Pedestrian target parameters – Situation A, Figure 12 a)
11.3.4.4 Pedestrian target parameters – Situation B, Figure 12 b)
11.3.4.5 Longitudinal distance (Slong)
11.3.4.6 Environmental parameters
11.3.4.7 Pass criteria
11.4 Drivable area test
11.4.1 Test setup
11.4.2 Vehicle parameters
11.4.3 Evaluation path parameters
11.4.4 Environmental parameters
11.4.5 Pass criteria for unblocked drivable area
11.4.6 Pass criteria for blocked drivable area
11.5 Minimal risk manoeuvre (MRM) test
11.5.1 Test setup
11.5.2 Vehicle parameters
11.5.3 Evaluation path parameters
11.5.4 Environmental parameters
11.5.5 MRM trigger
11.5.6 Pass criteria

Annex A (informative) Test speeds for hazardous situation tests

Annex B (informative) Example LSAD communication messages

Annex C (informative) Example LSAD system data recorder

Annex D (informative) LSAD system activities (experiment tests) in various countries

D.1 Japan
D.2 United States
D.3 United Kingdom
D.4 Europe
D.5 Australia
D.6 Taiwan

Page count: 43