ISO 15765-4:2021-07 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 4: Requirements for emissions-related systems

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and abbreviated terms 2
4.1 Symbols 2
4.2 Abbreviated terms 3

5 Conventions 4

6 Application 4
6.1 Vehicle communication initialisation sequence 4
6.1.1 OBDonUDS protocol identification 4
6.1.2 OBDonEDS protocol identification 4
6.1.3 Others 4
6.2 External test equipment communication initialisation sequence 4
6.3 Bit rate validation procedure 5
6.3.1 bitrateRecord 5
6.3.2 Bit rate validation 5
6.3.3 External test equipment error detection provisions 6
6.4 CAN identifier validation procedure 7
6.4.1 CAN identifier validation procedure OBDonEDS 7
6.4.2 CAN identifier validation procedure OBDonUDS 9
6.5 Support of ECUNAME reporting 11

7 Application layer (AL) 11

8 Session layer (SL) 12

9 Transport layer (TL) 12

10 Network layer (NL) 12
10.1 General 12
10.2 Parameter definitions 12
10.2.1 Timing parameter values 12
10.2.2 Definition of flow control parameter values 13
10.2.3 Maximum number of OBDonUDS or OBDonEDS ECUs 14
10.3 Addressing formats 15
10.3.1 Normal and normal fixed addressing format 15
10.3.2 Functional addressing 15
10.3.3 Physical addressing 15
10.4 CAN identifier requirements 16
10.4.1 External test equipment 16
10.4.2 OBDonUDS or OBDonEDS server/ECU 16
10.5 Mapping of diagnostic addresses 16

10.5.1 OBDonUDS/OBDonEDS CAN identifiers 16
10.5.2 11-bit CAN identifiers 17
10.5.3 29-bit CAN identifiers 18

11 Data link layer (DLL) 18

12 Physical layer (PHY) 18
12.1 General 18
12.2 Bit rates 19
12.3 CAN bit timing 19
12.3.1 Parameter values 19

12.3.2 Nominal bit rate 250 kbit/s 20
12.3.3 Nominal bit rate 500 kbit/s 20
12.4 External test equipment 21
12.4.1 Electrical parameters 21
12.4.2 Cable parameters 24

Bibliography 25