DIN EN ISO 15118-20:2022-12 (E)

Road vehicles - Vehicle to grid communication interface - Part 20: 2nd generation network layer and application layer requirements (ISO 15118-20:2022); English version EN ISO 15118-20:2022, only on CD-ROM

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 4

4 Abbreviated terms 12

5 Conventions 15
5.1 Definition of OSI based services 15
5.2 Requirement structure 15
5.3 Usage of references 16
5.4 Notation used for XML schema diagrams 16

6 Document overview 16

7 Basic requirements for V2G communication 17
7.1 General information 17
7.2 Service primitive concept of OSI layered architecture 18
7.2.1 Overview 18
7.2.2 Syntax of service primitives 18
7.3 Security concept 19
7.3.1 General 19
7.3.2 Certificate and key management 21
7.3.3 Number of root certificates and root validity 35
7.3.4 Support and application of TLS 37
7.3.5 Firewall 38
7.3.6 Protection of the cryptographic keys 38
7.3.7 Random number generation 40
7.4 V2G communication states and data link handling 42
7.5 Data link layer 46
7.5.1 Data link layer security for WLAN 46
7.6 Network link layer 51
7.6.1 General 51
7.6.2 Applicable RFCs, limitations and protocol parameter settings 51
7.6.3 IP addressing 53
7.7 Transport layer 54
7.7.1 Transmission control protocol (TCP) 54
7.7.2 User datagram protocol (UDP) 55
7.7.3 Transport layer security (TLS) 56
7.8 V2G transfer protocol 82
7.8.1 General information 82
7.8.2 Supported ports 83
7.8.3 Protocol data unit 84
7.9 Presentation layer 87
7.9.1 XML and efficient XML interchange (EXI) 87
7.9.2 Message security 90

7.10 Application layer 115
7.10.1 SECC discovery protocol 115
8 Application layer messages 128
8.1 General information and definitions 128
8.2 Protocol handshake definition 129
8.2.1 Handshake sequence 129
8.2.2 Message definition supportedAppProtocolReq and supportedAppProtocolRes 131
8.2.3 Semantics description supportedAppProtocol messages 132
8.2.4 Message examples 133
8.3 V2G message definition 134
8.3.1 Overview 134
8.3.2 General 135
8.3.3 Header definition 135
8.3.4 Request and response definitions 138
8.3.5 Complex data types 240
8.4 Service selection 361
8.4.1 General 361
8.4.2 General description of configuration parameters 362
8.4.3 Selection of service and service parameters 363
8.5 V2G communication timing 373
8.5.1 Overview 373
8.5.2 Common 373
8.5.3 DC service 374
8.5.4 Message sequence and communication session 374
8.5.5 Session setup and ready to charge 381
8.5.6 V2G message synchronization for AC and DC with IEC 61851-1 signalling 387
8.5.7 V2G message synchronization with IEC 61980-2 signalling for WPT 394
8.6 Message sequencing and error handling 394
8.6.1 Overview 394
8.6.2 Basic definitions for error handling 395
8.6.3 ResponseCode handling 395
8.6.4 Request-response message sequence requirements 406
8.6.5 Multiplexed communication 434
8.6.6 Message sequence diagrams 437
Annex A (normative) Schema definition 442
Annex B (normative) Certificate profiles 444
Annex C (normative) Specification of identifiers 498
Annex D (informative) ACDP 504
Annex E (informative) Basic PPD for interoperability 506
Annex F (informative) Message sequencing for renegotiation 509
Annex G (informative) Association of VAS client to V2G session 511
Annex H (informative) Application of certificates 512
Annex I (informative) Precision of measurements and tolerances 547
Annex J (informative) Absolute pricing examples 549