

DIN EN ISO 15118-20:2022-12 (E)

Road vehicles - Vehicle to grid communication interface - Part 20: 2nd generation network layer and application layer requirements (ISO 15118-20:2022); English version EN ISO 15118-20:2022, only on CD-ROM

Contents		Page
Foreword.....		v
Introduction.....		vi
1 Scope		1
2 Normative references		1
3 Terms and definitions.....		4
4 Abbreviated terms		12
5 Conventions		15
5.1 Definition of OSI based services		15
5.2 Requirement structure.....		15
5.3 Usage of references		16
5.4 Notation used for XML schema diagrams.....		16
6 Document overview.....		16
7 Basic requirements for V2G communication.....		17
7.1 General information		17
7.2 Service primitive concept of OSI layered architecture		18
7.2.1 Overview.....		18
7.2.2 Syntax of service primitives.....		18
7.3 Security concept.....		19
7.3.1 General		19
7.3.2 Certificate and key management		21
7.3.3 Number of root certificates and root validity.....		35
7.3.4 Support and application of TLS		37
7.3.5 Firewall		38
7.3.6 Protection of the cryptographic keys.....		38
7.3.7 Random number generation		40
7.4 V2G communication states and data link handling.....		42
7.5 Data link layer.....		46
7.5.1 Data link layer security for WLAN		46
7.6 Network link layer		51
7.6.1 General		51
7.6.2 Applicable RFCs, limitations and protocol parameter settings		51
7.6.3 IP addressing.....		53
7.7 Transport layer		54
7.7.1 Transmission control protocol (TCP)		54
7.7.2 User datagram protocol (UDP)		55
7.7.3 Transport layer security (TLS)		56
7.8 V2G transfer protocol.....		82
7.8.1 General information		82
7.8.2 Supported ports		83
7.8.3 Protocol data unit.....		84
7.9 Presentation layer		87
7.9.1 XML and efficient XML interchange (EXI)		87
7.9.2 Message security		90

7.10	Application layer.....	115
7.10.1	SECC discovery protocol.....	115
8	Application layer messages	128
8.1	General information and definitions.....	128
8.2	Protocol handshake definition	129
8.2.1	Handshake sequence	129
8.2.2	Message definition supportedAppProtocolReq and supportedAppProtocolRes	131
8.2.3	Semantics description supportedAppProtocol messages	132
8.2.4	Message examples.....	133
8.3	V2G message definition.....	134
8.3.1	Overview	134
8.3.2	General.....	135
8.3.3	Header definition	135
8.3.4	Request and response definitions.....	138
8.3.5	Complex data types.....	240
8.4	Service selection	361
8.4.1	General.....	361
8.4.2	General description of configuration parameters	362
8.4.3	Selection of service and service parameters.....	363
8.5	V2G communication timing.....	373
8.5.1	Overview	373
8.5.2	Common.....	373
8.5.3	DC service.....	374
8.5.4	Message sequence and communication session	374
8.5.5	Session setup and ready to charge.....	381
8.5.6	V2G message synchronization for AC and DC with IEC 61851-1 signalling	387
8.5.7	V2G message synchronization with IEC 61980-2 signalling for WPT	394
8.6	Message sequencing and error handling.....	394
8.6.1	Overview	394
8.6.2	Basic definitions for error handling.....	395
8.6.3	ResponseCode handling.....	395
8.6.4	Request-response message sequence requirements.....	406
8.6.5	Multiplexed communication	434
8.6.6	Message sequence diagrams	437
	Annex A (normative) Schema definition.....	442
	Annex B (normative) Certificate profiles.....	444
	Annex C (normative) Specification of identifiers.....	498
	Annex D (informative) ACDP	504
	Annex E (informative) Basic PPD for interoperability	506
	Annex F (informative) Message sequencing for renegotiation.....	509
	Annex G (informative) Association of VAS client to V2G session	511
	Annex H (informative) Application of certificates	512
	Annex I (informative) Precision of measurements and tolerances	547
	Annex J (informative) Absolute pricing examples	549