ISO 22733-1:2022-09 (E)

Road vehicles - Test method to evaluate the performance of autonomous emergency braking systems - Part 1: Car-to-car

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Variables 3
4.1 Reference system 3
4.2 Lateral offset 3
4.3 Variables to be measured 4

5 Equivalent vehicle target 4

6 Measuring equipment and data processing 4
6.1 General 4
6.2 Description 4
6.3 Transducer installation 5
6.4 Calibration 5
6.5 Data processing 5

7 Test conditions 5
7.1 General 5
7.2 General data 5
7.3 Test track 5
7.4 Weather conditions 6
7.5 Surroundings 6
7.6 VUT 6
7.6.1 General vehicle condition 6
7.6.2 AEB system settings 6
7.6.3 Deployable pedestrian protection systems 7
7.6.4 Tyres 7
7.6.5 Braking system 7
7.6.6 Other influencing system 7
7.6.7 Loading conditions of the vehicle 8

8 Test procedure 8
8.1 Test preparation 8
8.1.1 .....

Brake conditioning 8
8.1.2 Tyre conditioning 8
8.2 Test scenarios 9
8.3 Test conduct 10
8.4 Test execution 10
8.4.1 Speed 10
8.4.2 Validity criteria 10
8.4.3 End of test conditions 10

8.4.4 Determination of speed incremental steps 11

9 DBS tests (optional) 11

10 Performance metrics 11
10.1 Maximum speed of VUT at which collision is avoided: VVUT 11
10.2 Mean longitudinal acceleration of the VUT: AVUTmean 11
10.3 Maximum longitudinal acceleration of the VUT with DBS: AVUTmax 11
10.4 Average increase rate of longitudinal acceleration of VUT with DBS: AVUTincrease rate . 12
10.5 Impact speed of VUT at which collision first occurs: Vimpact 12
10.6 Activation time of AEBS: TAEB 12
10.7 Activation time of FCW: TFCW 12
10.8 Maximum yaw rate of the VUT: VUT 12
10.9 Lateral offset of the VUT: YVUT 12
10.10 Maximum steering wheel velocity of VUT: VUT 12

Annex A (informative) Brake application procedure 13

Annex B (informative) Test report 15

Bibliography 18