

# ISO 15500-13:2023-02 (E)

## Road vehicles - Compressed natural gas (CNG) fuel system components - Part 13: Pressure relief device (PRD)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Marking .....	3
5	Construction and assembly .....	3
6	Tests .....	4
6.1	Applicability .....	4
6.2	Hydrostatic strength .....	4
6.2.1	Housing .....	4
6.2.2	Fusible material .....	5
6.3	Leakage .....	5
6.4	Bending moment .....	5
6.5	Continued operation .....	6
6.5.1	Test procedure .....	6
6.5.2	Requirements .....	6
6.6	Accelerated life .....	6
6.6.1	General .....	6
6.6.2	Test procedure .....	6
6.6.3	Accelerated-life test temperature .....	6
6.6.4	Requirements .....	7
6.7	Benchtop activation .....	7
6.7.1	General .....	7
6.7.2	Thermally-activated relief devices .....	7
6.7.3	Series-combination relief devices .....	7
6.7.4	Parallel-combination relief devices .....	8
6.8	Thermal cycling .....	8
6.8.1	Test procedure .....	8
6.8.2	Requirements .....	8
6.9	Condensate-corrosion resistance .....	9
6.9.1	Test procedure .....	9
6.9.2	Test solution .....	9
6.10	Flow capacity .....	9
6.10.1	General .....	9
6.10.2	Test procedure .....	9
6.11	High-pressure activation and flow rate .....	10
6.11.1	General .....	10
6.11.2	Test setup .....	10
6.11.3	Test procedure .....	10
6.11.4	Acceptable results .....	10
6.11.5	Data analysis and availability .....	10
6.12	Water jet protection .....	10
6.12.1	General .....	10

6.12.2	Method of test .....	10
6.12.3	Acceptance criteria .....	10
6.13	Impact due to drop .....	11
7	Production batch inspection and acceptance testing .....	11
<b>Annex A (normative) Determination of fusible material yieldtemperature and PRD activation temperature .....</b>		<b>12</b>
<b>Bibliography .....</b>		<b>14</b>