

ISO 15500-13:2023-02 (E)

Road vehicles - Compressed natural gas (CNG) fuel system components - Part 13: Pressure relief device (PRD)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Marking | 3 |
| 5 | Construction and assembly | 3 |
| 6 | Tests | 4 |
| 6.1 | Applicability | 4 |
| 6.2 | Hydrostatic strength | 4 |
| 6.2.1 | Housing | 4 |
| 6.2.2 | Fusible material | 5 |
| 6.3 | Leakage | 5 |
| 6.4 | Bending moment | 5 |
| 6.5 | Continued operation | 6 |
| 6.5.1 | Test procedure | 6 |
| 6.5.2 | Requirements | 6 |
| 6.6 | Accelerated life | 6 |
| 6.6.1 | General | 6 |
| 6.6.2 | Test procedure | 6 |
| 6.6.3 | Accelerated-life test temperature | 6 |
| 6.6.4 | Requirements | 7 |
| 6.7 | Benchtop activation | 7 |
| 6.7.1 | General | 7 |
| 6.7.2 | Thermally-activated relief devices | 7 |
| 6.7.3 | Series-combination relief devices | 7 |
| 6.7.4 | Parallel-combination relief devices | 8 |
| 6.8 | Thermal cycling | 8 |
| 6.8.1 | Test procedure | 8 |
| 6.8.2 | Requirements | 8 |
| 6.9 | Condensate-corrosion resistance | 9 |
| 6.9.1 | Test procedure | 9 |
| 6.9.2 | Test solution | 9 |
| 6.10 | Flow capacity | 9 |
| 6.10.1 | General | 9 |
| 6.10.2 | Test procedure | 9 |
| 6.11 | High-pressure activation and flow rate | 10 |
| 6.11.1 | General | 10 |
| 6.11.2 | Test setup | 10 |
| 6.11.3 | Test procedure | 10 |
| 6.11.4 | Acceptable results | 10 |
| 6.11.5 | Data analysis and availability | 10 |
| 6.12 | Water jet protection | 10 |
| 6.12.1 | General | 10 |

| | | |
|---------------------|---|----|
| 6.12.2 | Method of test | 10 |
| 6.12.3 | Acceptance criteria | 10 |
| 6.13 | Impact due to drop | 11 |
| 7 | Production batch inspection and acceptance testing | 11 |
| Annex A (normative) | Determination of fusible material yieldtemperature and PRD activation temperature | 12 |
| Bibliography | | 14 |