

# ISO/TS 21957:2023-07 (E)

## Road vehicles - Visibility - Specifications and test procedures for head-up displays (HUD)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms related to vehicles .....</b>	<b>2</b>
<b>3.2</b>	<b>Terms related to the eyellipse and eyebox .....</b>	<b>4</b>
<b>3.3</b>	<b>Terms related to an HUD system .....</b>	<b>6</b>
<b>4</b>	<b>Abbreviated terms .....</b>	<b>12</b>
<b>5</b>	<b>Specification, verification, and reference point definition for HUD image evaluation .....</b>	<b>12</b>
<b>5.1</b>	<b>General .....</b>	<b>12</b>
<b>5.2</b>	<b>Eyellipse and the eye centroid location .....</b>	<b>12</b>
<b>5.3</b>	<b>Eyebox location .....</b>	<b>13</b>
<b>6</b>	<b>Evaluation, test and measurement .....</b>	<b>15</b>
<b>6.1</b>	<b>General .....</b>	<b>15</b>
<b>6.1.1</b>	<b>Measurement setup .....</b>	<b>15</b>
<b>6.2</b>	<b>Characterization of the HUD spatial and orientational aspects .....</b>	<b>24</b>
<b>6.2.1</b>	<b>Optical accommodation distance .....</b>	<b>24</b>
<b>6.2.2</b>	<b>Look down angle (LDA), look over angle (LOA) and image orientation coordinates .....</b>	<b>27</b>
<b>6.2.3</b>	<b>Display field of view (DFoV) .....</b>	<b>30</b>
<b>6.3</b>	<b>Luminance/brightness and contrast .....</b>	<b>31</b>
<b>6.3.1</b>	<b>Luminance and luminance non-uniformity measurement .....</b>	<b>31</b>
<b>6.3.2</b>	<b>Chromaticity measurement .....</b>	<b>33</b>
<b>6.3.3</b>	<b>Contrast ratio .....</b>	<b>33</b>
<b>6.4</b>	<b>Spatial characteristics .....</b>	<b>34</b>
<b>6.4.1</b>	<b>Resolution .....</b>	<b>34</b>
<b>6.4.2</b>	<b>Ghost image .....</b>	<b>37</b>
<b>6.4.3</b>	<b>Distortion and rotation .....</b>	<b>40</b>
<b>6.4.4</b>	<b>Deviation ratio of aspect ratio .....</b>	<b>43</b>
<b>6.5</b>	<b>Others .....</b>	<b>43</b>
<b>6.5.1</b>	<b>General .....</b>	<b>43</b>
<b>6.5.2</b>	<b>Care and considerations .....</b>	<b>43</b>
<b>6.5.3</b>	<b>Capability of geometric adjustability to the driver head position .....</b>	<b>43</b>
<b>6.5.4</b>	<b>Display visual performance adjustability .....</b>	<b>44</b>
<b>6.5.5</b>	<b>Automatic adjustment accuracy and latency .....</b>	<b>44</b>
<b>7</b>	<b>Laboratory assessment on vehicle setup and eyellipse location (procedure for measurement of HUD virtual image) .....</b>	<b>45</b>
<b>7.1</b>	<b>General .....</b>	<b>45</b>
<b>7.2</b>	<b>Vehicle setup .....</b>	<b>45</b>
<b>7.3</b>	<b>Mannequin/visual reference eye point installation .....</b>	<b>46</b>
<b>7.4</b>	<b>External environmental condition .....</b>	<b>46</b>
<b>7.4.1</b>	<b>External light environment .....</b>	<b>46</b>
<b>7.4.2</b>	<b>Road surface ahead .....</b>	<b>47</b>

<b>8</b>	<b>Environmental test .....</b>	<b>48</b>
<b>8.1</b>	<b>General .....</b>	<b>48</b>
<b>8.1.1</b>	<b>Measurement setup .....</b>	<b>48</b>
<b>8.1.2</b>	<b>Measurement procedure .....</b>	<b>49</b>
<b>8.1.3</b>	<b>Protection of HUD unit against foreign objects, liquids .....</b>	<b>49</b>
<b>9</b>	<b>Consideration when using HUD .....</b>	<b>49</b>
	<b>Annex A (informative) Eyellipse versus eyebox .....</b>	<b>50</b>
	<b>Annex B (informative) Subjective evaluation for a 3D HUD .....</b>	<b>53</b>
	<b>Annex C (informative) Environmental test of the HUD engine .....</b>	<b>65</b>
	<b>Annex D (informative) Environmental interfering factors in HUD performance for windscreen .....</b>	<b>69</b>
	<b>Annex E (informative) Consideration on additional factor affecting the HUD performance/ visibility</b>	<b>70</b>
	<b>Annex F (informative) HUD using alternative image generation technologies .....</b>	<b>72</b>
	<b>Bibliography .....</b>	<b>75</b>