ISO 22574:2023-08 (E)

Road vehicles - Brake linings friction materials - Visual inspection

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Characteristic features for friction materials 1
4.1 Characteristic features for disc brake pads 1
4.1.1 Gapping between material and plate 1
4.1.2 Edge chipping 2
4.1.3 Splits 2
4.1.4 Minor splits 3
4.1.5 Plucked and indented spigots 3
4.1.6 Poor consolidated spigot holes 3
4.1.7 Excess adhesive on plate 4
4.1.8 Material flash on plate 4
4.1.9 Abrasive coating 5
4.1.10 Anti-noise coating runs 5
4.1.11 Skin crazing 6
4.1.12 Underlayer distribution 6
4.1.13 Marking 7
4.1.14 Unground material surface 7
4.1.15 Paint on friction material surface 7
4.1.16 Surface blisters 8
4.1.17 Surface indentations 8
4.1.18 Grinding marks on friction surface 9
4.1.19 High porosity area 9
4.1.20 Poorly consolidated friction material 10
4.1.21 Surface contamination with foreign matters 10
4.1.22 Surface contamination with similar friction materials 11
4.1.23 Friction surface structure 11
4.1.24 Plate scratched and dents 12
4.1.25 Blanking burrs 12
4.1.26 Deformation by blanking and edge chipping at functional area 13
4.1.27 Edge shipping at pin area 13
4.1.28 Pinholes (Side-cut cavity) 14
4.1.29 Grinding marks on the carrier 14
4.1.30 Spring holder defects 15
4.1.31 Surface deepening 15
4.1.32 Cold laps 16
4.2 Characteristic features for drum brake linings 16
4.2.1 Chipped edges/corners 16
4.2.2 Edge splits 17
4.2.3 Drill hole chipping at lining ends 18
4.2.4 Drill hole burrs inside the surface 18
4.2.5 Drill hole burrs outside the surface 18
4.2.6 Cracks radiating from the rivet hole 19
4.2.7 Paint on surface - Lining for riveting and bonding 19

4.2.8 Surface cracks 20
4.2.9 Marking 20
4.2.10 Moulding skin on inside radius surface - linings for bonding and riveting 21
4.2.11 Moulding skin on outside radius surface - linings for riveting or bonding 21
4.2.12 Surface blisters 22
4.2.13 Surface grind marks 22
4.2.14 Pitted surface (plucked surface) 23
4.2.15 Surface structure 23
4.2.16 Poor consolidated friction material 24
4.2.17 Inside surface indentations 24
4.2.18 Outside surface indentations 25
4.2.19 Concentration of self-contained ingredients unless typical of the formulation 26
4.2.20 High porosity area 27
4.2.21 Metal wire or plastic reinforcement 27
4.2.22 Foreign matter friction surface inclusion 28
4.3 Characteristic features for bonded lined shoes 28
4.3.1 Lining overhang on shoe platform edge 28
4.3.2 Faulty shoes 29
4.3.3 Restricted lever movement 29
4.3.4 Stencilled information 30
4.3.5 Excess adhesive exudation over shoe platform edges 31
4.3.6 Excess adhesive exudation from lining ends 31
4.3.7 Excess primer 32
4.3.8 Lining surface condition 32
4.3.9 Gaps between linings and shoe platform 34