

ISO 12156-1:2023-09 (E)

Diesel fuel - Assessment of lubricity using the high-frequency reciprocating rig (HFRR) - Part 1: Test method

| Contents | | Page |
|---|--|-------------|
| Foreword..... | | iv |
| Introduction..... | | v |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Principle | | 2 |
| 5 Reagents and materials | | 2 |
| 6 Apparatus | | 3 |
| 7 Sampling | | 5 |
| 8 Preparation and calibration | | 6 |
| 8.1 Preparation of apparatus..... | | 6 |
| 8.1.1 Test plates and balls..... | | 6 |
| 8.1.2 Hardware..... | | 6 |
| 8.2 Calibration and correction..... | | 6 |
| 8.2.1 Temperature..... | | 6 |
| 8.2.2 Frequency..... | | 6 |
| 8.2.3 Stroke length..... | | 6 |
| 8.2.4 Test duration..... | | 6 |
| 8.2.5 Test rig performance..... | | 6 |
| 9 Test procedure | | 7 |
| 10 Measurement of wear scar | | 8 |
| 11 Test results | | 8 |
| 12 Precision | | 8 |
| 12.1 General..... | | 8 |
| 12.2 Repeatability, <i>r</i> | | 8 |
| 12.3 Reproducibility, <i>R</i> | | 9 |
| 13 Test report | | 9 |
| Annex A (informative) Measurement of HFRR wear scars | | 10 |
| Bibliography | | 13 |