

# ISO 22733-2:2023-11 (E)

## Road vehicles - Test method to evaluate the performance of autonomous emergency braking systems - Part 2: Car to pedestrian

---

<b>Contents</b>		<b>Page</b>
Foreword		v
Introduction		vi
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>1</b>
<b>4</b>	<b>Reference system and variables</b>	<b>4</b>
4.1	Coordinate system	4
4.2	Lateral path errors	5
4.3	Profiles for impact speed determination	5
<b>5</b>	<b>Variables to be measured</b>	<b>6</b>
<b>6</b>	<b>Measuring equipment</b>	<b>7</b>
6.1	Description	7
6.2	Transducer installation	7
6.3	Calibration	7
6.4	Data processing	8
<b>7</b>	<b>Test conditions</b>	<b>8</b>
7.1	General	8
7.2	General data	8
7.3	Test track	8
7.4	Weather conditions	8
7.5	Surroundings	8
7.6	VUT	8
7.6.1	General vehicle condition	8
7.6.2	AEBS settings	8
7.6.3	Deployable pedestrian protection systems	8
7.6.4	Tyres	8
7.6.5	Braking system	9
7.6.6	Other influencing system	9
7.6.7	Loading conditions	9
<b>8</b>	<b>Test procedures</b>	<b>9</b>
8.1	Test preparation	9
8.1.1	Brake conditioning	9
8.1.2	Tyre conditioning	9
8.2	Test scenarios	9
8.3	Test conduct	13
8.4	Test execution	13
8.4.1	Speeds	13
8.4.2	Validity criteria	14
8.4.3	End of test conditions	14
<b>9</b>	<b>Performance metrics</b>	<b>14</b>
9.1	Performance metrics for test until collision	14
9.1.1	Speed of VUT ( $V_{VUT}$ ) and speed of VUT at which collision is last avoided ( $V_{VUT}^{cla}$ )	15
9.1.2	Impact speed of VUT at which collision first occurs: $V_{IMPACT}$	15
9.1.3	Activation time of AEBS ( $T_{AEB}$ ) and activation time of AEBS at which collision is last avoided ( $T_{AEB}^{cla}$ )	15

9.1.4	Activation time of FCW ( $T_{FCW}$ ) and activation time of FCW at which collision is last avoided ( $(T_{FCW})_{cla}$ )	15
9.1.5	Mean longitudinal acceleration of the VUT ( $A_{VUT}$ ) and mean longitudinal acceleration of the VUT at which collision is last avoided ( $(A_{VUT})_{cla}$ )	15
9.1.6	Maximum yaw rate of the VUT ( $(\dot{\psi}_{VUT})_{max}$ ) and maximum yaw rate of the VUT at which collision is last avoided ( $(\dot{\psi}_{VUT})_{max,cla}$ )	15
9.1.7	Lateral path error of the VUT ( $Y_{VUT}$ ) and lateral path error of the VUT at which collision is last avoided ( $(Y_{VUT})_{cla}$ )	15
9.1.8	Maximum steering wheel velocity of VUT ( $(\dot{\Omega}_{VUT})_{max}$ ) and maximum steering wheel velocity at which collision is last avoided ( $(\dot{\Omega}_{VUT})_{max,cla}$ )	15
9.2	Performance metrics for test until the designated maximum speed where no collision occurs	16
9.2.1	Speed of VUT ( $V_{VUT}$ ) until the designated maximum speed ( $(V_{VUT})_{ds}$ )	16
9.2.2	Activation time of AEBS ( $T_{AEB}$ ) and activation time of AEBS at the designated maximum speed ( $(T_{AEB})_{dms}$ )	16
9.2.3	Activation time of FCW ( $T_{FCW}$ ) and activation time of FCW at the designated maximum speed ( $(T_{FCW})_{dms}$ )	16
9.2.4	Mean longitudinal acceleration of the VUT ( $A_{VUT}$ ) and mean longitudinal acceleration of the VUT at the designated maximum speed ( $(A_{VUT})_{dms}$ )	16
9.2.5	Maximum yaw rate of the VUT ( $(\dot{\psi}_{VUT})_{max}$ ) and maximum yaw rate of the VUT at the designated speed ( $(\dot{\psi}_{VUT})_{max,dms}$ )	17
9.2.6	Lateral offset of the VUT ( $Y_{VUT}$ ) and lateral offset of the VUT at the designated maximum speed ( $(Y_{VUT})_{dms}$ )	17
9.2.7	Maximum steering wheel velocity of VUT ( $(\dot{\Omega}_{VUT})_{max}$ ) and maximum steering wheel velocity at the designated maximum speed ( $(\dot{\Omega}_{VUT})_{max,dms}$ )	17
9.3	Performance metrics for test until the designated maximum speed where collision occurs	17
9.3.1	Speed of VUT ( $V_{VUT}$ ) and speed of VUT at which collision is last avoided ( $(V_{VUT})_{cla}$ )	18
9.3.2	Impact speed of VUT at which collision first occurs: $V_{IMPACT}$	18
9.3.3	Activation time of AEBS ( $T_{AEB}$ ) and activation time of AEBS at which collision is last avoided ( $(T_{AEB})_{cla}$ )	18
9.3.4	Activation time of FCW ( $T_{FCW}$ ) and activation time of FCW at which collision is last avoided ( $(T_{FCW})_{cla}$ )	18
9.3.5	Mean longitudinal acceleration of the VUT ( $A_{VUT}$ ) and mean longitudinal acceleration of the VUT at which collision is last avoided ( $(A_{VUT})_{cla}$ )	18
9.3.6	Maximum yaw rate of the VUT ( $(\dot{\psi}_{VUT})_{max}$ ) and maximum yaw rate of the VUT at which collision is last avoided: ( $(\dot{\psi}_{VUT})_{max,cla}$ )	18
9.3.7	Lateral offset of the VUT ( $Y_{VUT}$ ) and lateral offset of the VUT at which collision is last avoided ( $(Y_{VUT})_{cla}$ )	18
9.3.8	Maximum steering wheel velocity of VUT ( $(\dot{\Omega}_{VUT})_{max}$ ) and maximum steering wheel velocity at which collision is last avoided ( $(\dot{\Omega}_{VUT})_{max,cla}$ )	18
	<b>Bibliography</b>	<b>20</b>