DIN/TS 70121:2024-11 (E)

Electromobility - Digital communication between a d.c. EV charging station and an electric vehicle for control of d.c. charging in the Combined Charging System; Text in English

Inhalt

Seite

Foreword ... 11

Introduction ... 12

1 Scope ... 13

2 Normative references ... 13

3 Terms and definitions ... 15

4 Symbols and abbreviations ... 20

5 Relation to other standards ... 22

6 Conventions ... 22
6.1 Definition of OSI based services ... 22
6.2 Requirement structure ... 22
6.2.1 Requirement format ... 22
6.2.2 Applicability ... 23
6.2.3 Usage of RFC references ... 23
6.3 Notation used for XML schema diagrams ... 23

7 DC charging system architecture ... 24
7.1 System schematics of DC charging system ... 24
7.2 Pilot function ... 24
7.3 Communication stack ... 24

8 EV-EVSE communication ... 25
8.1 Basic requirements for V2G communication ... 25
8.1.1 General information and definitions ... 25
8.2 Service primitive concept of OSI layered architecture ... 25
8.2.1 Overview ... 25
8.2.2 Syntax of service primitives ... 26
8.3 Physical and Data Link Layer ... 26
8.3.1 System architecture ... 26
8.3.2 Connection coordination ... 29
8.3.3 EV – EVSE matching process ... 29
8.3.4 Timings, parameters and error handling ... 48
8.3.5 Error handling ... 52
8.3.6 EMC requirements ... 64
8.3.7 Coupling circuit ... 65
8.3.8 Layer 2 interfaces ... 74
8.3.9 Sleep and Wake-up Handling ... 75
8.4 V2G communication states ... 76
8.4.1 V2G communication of the EVCC ... 76
8.4.2 V2G communication of the SECC ... 78
8.5 Network layer ... 81
8.5.1 General ... 81
8.5.2 Applicable RFCs and limitations and protocol parameter settings ... 81
8.5.3 IP addressing ... 82
8.5.4 Network Layer service primitive — N–IP_Address.indication ... 83

8.5.5 SECC discovery 83
8.6 Transport Layer 84
8.6.1 Transmission control protocol (TCP) 84
8.6.2 User datagram protocol (UDP) 85
8.7 V2G transfer protocol 85
8.7.1 General information 85
8.7.2 Supported ports 85
8.7.3 Protocol data unit 86
8.8 Presentation layer 89
8.8.1 XML and efficient XML interchange (EXI) 89
8.9 Application layer 92
8.9.1 Vehicle to grid application layer messages 92
8.9.2 Application layer service primitives 92
8.9.3 SECC Discovery protocol 95

9 Application layer messages 101
9.1 General information and definitions 101
9.2 Protocol handshake 101
9.2.1 Handshake request-response message pair 101
9.2.2 Message definition supportedAppProtocolReq and supportedAppProtocolRes 102
9.3 Message structure 106
9.3.1 Overview 106
9.3.2 Message definition 106
9.3.3 Message header definition 108
9.3.4 Message body definition 109
9.4 BodyElement Definitions 109
9.4.1 Common Messages 109
9.4.2 DC messages 124
9.5 Complex data types 133
9.5.1 Overview 133
9.5.2 Common types 133
9.5.3 DC specific types 143
9.5.4 Use of optional schema elements 152
9.6 Session timing and error handling 157
9.6.1 Overview 157
9.6.2 Message sequence and performance timing definitions 158
9.6.3 EVCC timing and error handling for request-response message pairs 162
9.6.4 SECC timing and error handling for response-request message sequence 162
9.6.5 V2G communication session timing definitions 163
9.7 Message sequences 169
9.7.1 Protocol flow stages and associated messages 169
9.7.2 Basic definitions for error handling 170
9.7.3 Response code usage by the SECC 170
9.7.4 Request-response message sequence requirements 172
9.7.5 Message sequence example of successful DC charging session 186

Annex A (normative) XML Schema application layer messages 189
A.1 Overview 189
A.2 V2G_CI_AppProtocol.xsd 189
A.3 V2G_CI_MsgDef.xsd 190
A.4 V2G_CI_MsgHeader.xsd 191
A.5 V2G_CI_MsgBody.xsd 191
A.6 V2G_CI_MsgDataTypes.xsd 201
A.7 xmldsig-core-schema.xsd 214

Annex B (informative) Difference between multi-network broadcast, broadcast and unicast 220

Annex C (informative) SLAC attenuation calculation example 221

Annex D (informative) Begriffe 223

Annex E (informative) Modified requirements **229**
Bibliography **231**

Figures

Figure 1 — Communication relationship between EV, EVSE, and BS **13**
Figure 2 — Protocol stack for DC charging control without security **25**
Figure 3 — OSI layered architecture principles **25**
Figure 4 — EVSE discovery process from EV side **32**
Figure 5 — Matching state machine **33**
Figure 6 — Sequence chart of HomePlug Green PHY matching process **34**
Figure 7 — Example of toggle sequence with 2 toggles **41**
Figure 8 —Matching timing sequence chart **50**
Figure 9 — CM_SLAC_PARM.REQ/CNF sequence chart **53**
Figure 10 — Signal strength measurement Sequence Chart **55**
Figure 11 — Matching validation sequence chart **58**
Figure 12 — Logical network parameter exchange sequence chart **60**
Figure 13 — Joining the logical network sequence chart **62**
Figure 14 — Amplitude map exchange sequence chart **63**
Figure 15 — Implementation of parallel injection **65**
Figure 16 — HomePlug Green PHY-transmission path example with SLAC relevant attenuations and calculations **68**
Figure 17 — Measurement setup **70**
Figure 18 — Implementation example with a HomePlug Green PHY coupling transformer **72**
Figure 19 — Overview sources of crosstalk **73**
Figure 20 — Example of valid crosstalk filter in the case of HPGP signals **74**
Figure 21 —OSI Layer 1-2 overview **74**
Figure 22 — Overview V2G communication states EVCC **78**
Figure 23 — Overview V2G communication states SECC **80**
Figure 24 — V2GTP message structure **86**
Figure 25 — V2GTP message header structure **87**

Figure 26 — V2GTP generic header handler **89**

Figure 27 — Basic concept of EXI **91**

Figure 28 — SECC discovery request message payload **97**

Figure 29 — SECC discovery response message payload **99**

Figure 30 — Schema Diagram — supportedAppProtocolReq **103**

Figure 31 — Schema Diagram — supportedAppProtocolRes **103**

Figure 32 — Schema diagram — V2G message **107**

Figure 33 — Schema diagram — message header **108**

Figure 34 — Schema diagram — message body **109**

Figure 35 — Schema diagram — SessionSetupReq **110**

Figure 36 — Schema diagram — SessionSetupRes **111**

Figure 37 — Schema diagram — ServiceDiscoveryReq **112**

Figure 38 — Schema diagram — ServiceDiscoveryRes **114**

Figure 39 — Schema diagram — ServicePaymentSelectionReq **115**

Figure 40 — Schema diagram — ServicePaymentSelectionRes **115**

Figure 41 — Schema diagram — ContractAuthenticationReq **116**

Figure 42 — Schema diagram — ContractAuthenticationRes **117**

Figure 43 — Schema diagram — ChargeParameterDiscoveryReq **118**

Figure 44 — Schema diagram — ChargeParameterDiscoveryRes **119**

Figure 45 — Schema diagram — PowerDeliveryReq **121**

Figure 46 — Schema diagram — PowerDeliveryRes **122**

Figure 47 — Schema diagram — SessionStopReq **123**

Figure 48 — Schema diagram — SessionStopRes **123**

Figure 49 — Schema diagram — CableCheckReq **124**

Figure 50 — Schema diagram — CableCheckRes **125**

Figure 51 — Schema diagram — PreChargeReq **126**

Figure 52 — Schema diagram — PreChargeRes **126**

Figure 53 — Schema diagram — CurrentDemandReq **128**

Figure 54 — Schema diagram — CurrentDemandRes **130**

Figure 55 — Schema diagram — WeldingDetectionReq 132

Figure 56 — Schema diagram — WeldingDetectionRes 133

Figure 57 — Schema diagram — ServiceTagType 133

Figure 58 — Schema diagram — ServiceType 134

Figure 59 — Schema diagram — ServiceChargeType 135

Figure 60 — Schema diagram — PhysicalValueType 136

Figure 61 — Schema diagram — PaymentOptionsType 137

Figure 62 — Schema diagram — XML Schema Definition for the ChargingProfileType 138

Figure 63 — Schema diagram — ProfileEntryType 138

Figure 64 — Schema diagram — SAScheduleListType 139

Figure 65 — Schema diagram — SAScheduleTupleType 140

Figure 66 — Schema diagram — PMaxScheduleType 141

Figure 67 — Schema diagram — PMaxScheduleEntryType 141

Figure 68 — Schema diagram — RelativeTimeIntervalType 142

Figure 69 — Schema diagram — SelectedServiceListType 143

Figure 70 — Schema Diagram — SelectedServiceType 143

Figure 71 — Schema diagram — DC_EVSEStatusType 144

Figure 72 — Schema diagram — DC_EVStatusType 146

Figure 73 — Schema diagram — DC_EVChargeParameterType 148

Figure 74 — Schema diagram — DC_EVSEChargeParameterType 150

Figure 75 — Schema diagram — DC_EVPowerDeliveryParameterType 151

Figure 76 — Message sequence and performance timing 161

Figure 77 — V2G communication session timing 168

Figure 78 — Initialization sequence between EV and EVSE 186

Figure 79 — Initialization sequence (cont.) between EV and EVSE 187

Figure 80 — Pre-charge and energy transfer sequence between EV and EVSE 188

Figure 81 — Welding Detection and terminate charging sequence between EV and EVSE 188

Figure A.1 — Dependency chart of the V2G CI XML schema definitions 189

Figure C.1 — SLAC attenuation calculation example 222

Tables

Table 1 — ROBO modes and PHY data rate 28

Table 2 — SLAC MME parameter values 35

Table 3 — EV_Discovering_Status definition 40

Table 4 — MME parameters for Validation, first request-response 43

Table 5 — MME parameters for validation, second request-response 44

Table 6 — CM_AMP_MAP.REQ parameters 47

Table 7 — CM_AMP_MAP.CNF parameters 47

Table 8 — Timings and parameters 51

Table 9 — Notched carriers 64

Table 10 — Signal requirements for parallel HomePlug Green PHY injection to Control Pilot 66

Table 11 — Component values of HomePlug Green PHY coupling Implementation example 72

Table 12 — Mandatory ICMP message set 82

Table 13 — N-IP_Address.indication service primitive 83

Table 14 — Supported ports for V2GTP 85

Table 15 — Generic V2GTP header structure 87

Table 16 — Overview on V2GTP payload types 88

Table 17 — Excluded EXI coding options 91

Table 18 — EXI profile settings 91

Table 19 — A-Data.confirmation service primitive 92

Table 20 — A-Data.response service primitive 93

Table 21 — A-Data.request service primitive 94

Table 22 — A-Data.indication service primitive 95

Table 23 — Payload type SECC discover request message 98

Table 24 — N-SECC_Address.indication service primitive 100

Table 25 — Semantics and type definition for supportedAppProtocol message elements 103

Table 26 — Semantics and type definition for a V2G message 107

Table 27 — Semantics and type definition for a V2G message header 109

Table 28 — Semantics and type definition for a V2G message body 109

Table 29 — Semantics and type definition for SessionSetupReq **111**

Table 30 — Semantics and type definition for SessionSetupRes **111**

Table 31 — Semantics and type definition for ServiceDiscoveryReq **113**

Table 32 — Semantics and type definition for ServiceDiscoveryRes **114**

Table 33 — Semantics and type definition for ServicePaymentSelectionReq **115**

Table 34 — Semantics and type definition for ServicePaymentSelectionRes **115**

Table 35 — Semantics and type definition for ContractAuthenticationReq **116**

Table 36 — Semantics and type definition for ContractAuthenticationRes **117**

Table 37 — Semantics and type definition for ChargeParameterDiscoveryReq **118**

Table 38 — Semantics for EVRequestedEnergyTransferType **118**

Table 39 — Semantics and type definition for ChargeParameterDiscoveryRes **120**

Table 40 — Semantics and type definition for PowerDeliveryReq **121**

Table 41 — Semantics and type definition for PowerDeliveryRes **122**

Table 42 — Semantics and type definition for SessionStopRes **123**

Table 43 — Semantics and type definition for CableCheckReq **124**

Table 44 — Semantics and type definition for CableCheckRes **125**

Table 45 — Semantics and type definition for PreChargeReq **126**

Table 46 — Semantics and type definition for PreChargeRes **127**

Table 47 — Semantics and type definition for CurrentDemandReq **129**

Table 48 — Semantics and type definition for CurrentDemandRes **131**

Table 49 — Semantics and type definition for WeldingDetectionReq **132**

Table 50 — Semantics and type definition for WeldingDetectionRes **133**

Table 51 — Semantics and type definition for ServiceTagType **134**

Table 52 — Semantics and type definition for ServiceType **135**

Table 53 — Semantics and type definition for ServiceChargeType **135**

Table 54 — Semantics for EVSESupportedEnergyTransferType **136**

Table 55 — Semantics and type definition for PhysicalValueType **137**

Table 56 — Semantics and type definition for PaymentOptionsType **137**

Table 57 — Semantics and type definition for ChargingProfileType **138**

Table 58 — Semantics and type definition for ProfileEntryType **139**

Table 59 — Semantics and type definition for SAScheduleListType **139**

Table 60 — Semantics and type definition for SAScheduleTupleType **140**

Table 61 — Semantics and type definition for PMaxScheduleType **141**

Table 62 — Semantics and type definition for PMaxScheduleEntryType **142**

Table 63 — Semantics and type definition for RelativeTimeIntervalType **142**

Table 64 — Semantics and type definition for SelectedServiceListType **143**

Table 65 — Semantics and type definition for SelectedServiceType **143**

Table 66 — Semantics and type definition for DC_EVSEStatusType **144**

Table 67 — Semantics & Types of Elements in the isolationLevelType **145**

Table 68 — Semantics and type definition for DC_EVSEStatusCodeType **145**

Table 69 — Semantics and type definition for DC_EVStatusType **146**

Table 70 — Semantics and type definition for EVErrorCodeType **147**

Table 71 — Semantics and type definition for DC_EVChargeParameterType **149**

Table 72 — Semantics and type definition for DC_EVSEChargeParameterType **151**

Table 73 — Semantics and type definition for DC_EVPowerDeliveryParameterType **152**

Table 74 — Optional schema elements **152**

Table 75 — EVCC and SECC timers, timeouts, performance times **158**

Table 76 — EVCC and SECC message timeouts and performance times **160**

Table 77 — EVCC and SECC V2G communication session timing parameters **166**

Table 78 — EVCC and SECC V2G communication session timing parameter values **167**

Table 79 — Overview on the use of ResponseCodes **171**

Table E.1 — Modified requirements **229**