

# ISO 6621-4:2024-05 (E)

## Internal combustion engines - Piston rings - Part 4: General specifications

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Piston ring codes .....	1
5	Designation of piston rings .....	4
5.1	Designation elements and order .....	4
5.1.1	General .....	4
5.1.2	Mandatory elements .....	4
5.1.3	Measurement principles .....	5
5.1.4	Additional elements .....	5
5.1.5	Elements for additional marking .....	5
5.2	Designation examples .....	5
5.2.1	Designation example of a piston ring in accordance with ISO 6622-1 .....	5
5.2.2	Designation example of a piston ring in accordance with ISO 6624-1 .....	5
5.2.3	Designation example of a piston ring in accordance with ISO 6626-1 .....	6
6	Designation of piston rings .....	6
6.1	General .....	6
6.2	Mandatory topside identification marking .....	6
6.3	Additional marking .....	7
7	General characteristics .....	7
7.1	Ring shape .....	7
7.2	Light tightness .....	8
7.3	Closed gap .....	8
7.4	Tangential force, $F_t$ , and diametral force, $F_d$ , of single piece piston rings .....	8
7.4.1	Calculation of $F_t$ , and $F_d$ values in dimension tables of dimensional standards .....	8
7.4.2	Correction of $F_t$ , and $F_d$ values .....	9
7.4.3	Examples for correction of $F_t$ and $F_d$ .....	10
7.5	Tangential force $F_t$ of multipiece oil control rings as specified in ISO 6626-1, ISO 6626-2, and ISO 6626-3 .....	12
7.5.1	General .....	12
7.5.2	Rounding of values .....	12
7.5.3	Examples for calculating tangential force $F_t$ .....	12
7.6	Tangential force $F_t$ of expander/rail oil control rings as specified in ISO 6627 .....	13
7.6.1	General .....	13
7.6.2	Example for calculating the tangential force $F_t$ -- Selected type of piston ring: ISO 6627 -ES3 - 85 × 3 - MC67 MC68/CR1 PNH .....	13
8	Notches for preventing ring rotation .....	13
8.1	Ring joint with internal notch (only for compression rings as specified in ISO 6622 and ISO 6624) .....	13
8.2	Ring joint with side notch (only for compression rings as specified in ISO 6622) .....	15

<b>9</b>	<b>Machining of surfaces</b> .....	<b>16</b>
<b>9.1</b>	<b>Peripheral surfaces</b> .....	<b>16</b>
<b>9.2</b>	<b>Side faces</b> .....	<b>16</b>
<b>9.3</b>	<b>Other surfaces</b> .....	<b>16</b>
<b>10</b>	<b>Plated, coated, and treated surfaces</b> .....	<b>17</b>
<b>10.1</b>	<b>Chromium plating on peripheral and side surfaces</b> .....	<b>17</b>
<b>10.1.1</b>	<b>General</b> .....	<b>17</b>
<b>10.1.2</b>	<b>Chromium plating thickness</b> .....	<b>17</b>
<b>10.1.3</b>	<b>Chromium plated rings of fully faced design</b> .....	<b>17</b>
<b>10.1.4</b>	<b>Chromium plated rings of semi-inlaid design</b> .....	<b>17</b>
<b>10.1.5</b>	<b>Chromium plated rings of inlaid design</b> .....	<b>18</b>
<b>10.1.6</b>	<b>Side Chromium plated rings design</b> .....	<b>19</b>
<b>10.1.7</b>	<b>Radius, chamfer and dimensions of peripheral edges of chromium plated rings</b> .....	<b>19</b>
<b>10.1.8</b>	<b>Peripheral edges at the gap of chromium plated rings and rails</b> .....	<b>20</b>
<b>10.1.9</b>	<b>Hardness of chromium plating</b> .....	<b>21</b>
<b>10.2</b>	<b>Spray-coated peripheral surfaces</b> .....	<b>21</b>
<b>10.2.1</b>	<b>Codes</b> .....	<b>21</b>
<b>10.2.2</b>	<b>Spray-coating thickness</b> .....	<b>21</b>
<b>10.2.3</b>	<b>Spray-coated rings of fully faced design</b> .....	<b>21</b>
<b>10.2.4</b>	<b>Spray-coated rings of semi-inlaid design</b> .....	<b>21</b>
<b>10.2.5</b>	<b>Spray-coated rings of inlaid design</b> .....	<b>22</b>
<b>10.2.6</b>	<b>Radius, chamfer of peripheral edges of spray-coated rings</b> .....	<b>23</b>
<b>10.2.7</b>	<b>Peripheral edges at gap of spray-coated rings</b> .....	<b>23</b>
<b>10.2.8</b>	<b>Hardness of spray-coating</b> .....	<b>24</b>
<b>10.3</b>	<b>Nitride surfaces</b> .....	<b>24</b>
<b>10.3.1</b>	<b>Codes</b> .....	<b>24</b>
<b>10.3.2</b>	<b>Nitride case depth</b> .....	<b>24</b>
<b>10.3.3</b>	<b>Radius and dimensions of outside and inside edges of nitride steel rings</b> .....	<b>25</b>
<b>10.3.4</b>	<b>Peripheral edges at the gap of nitride steel rings and rails</b> .....	<b>25</b>
<b>10.4</b>	<b>Treated surfaces</b> .....	<b>26</b>
<b>10.4.1</b>	<b>Ferro-oxidized all over -- Code FE -- Coating thickness (0,001 to 0,005) mm</b> .....	<b>26</b>
<b>10.4.2</b>	<b>Phosphated all over -- Code PO -- Coating thickness 0,002 mm min</b> .....	<b>26</b>
<b>10.4.3</b>	<b>Phosphated all over -- Code PR -- Coating thickness 0,002 mm max</b> .....	<b>26</b>
<b>10.5</b>	<b>Physical vapour deposition coating (PVD)</b> .....	<b>26</b>
<b>10.5.1</b>	<b>Codes</b> .....	<b>26</b>
<b>10.5.2</b>	<b>PVD coating</b> .....	<b>26</b>
<b>10.5.3</b>	<b>PVD coating thickness</b> .....	<b>26</b>
<b>10.5.4</b>	<b>Hardness of PVD coating</b> .....	<b>26</b>
<b>10.5.5</b>	<b>Peripheral edges at the gap of PVD-coated rings and rails</b> .....	<b>27</b>
<b>11</b>	<b>Miscellaneous</b> .....	<b>27</b>
<b>11.1</b>	<b>Cleanliness</b> .....	<b>27</b>
<b>11.2</b>	<b>Corrosion protection</b> .....	<b>27</b>
<b>11.3</b>	<b>Packaging</b> .....	<b>27</b>
<b>12</b>	<b>Traceability (optional)</b> .....	<b>27</b>
	<b>Bibliography</b> .....	<b>28</b>