

# ISO 11898-1:2024-05 (E)

## Road vehicles - Controller area network (CAN) - Part 1: Data link layer and physical coding sublayer

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols and abbreviated terms .....	6
5	Basic concepts of CAN .....	8
5.1	CAN properties .....	8
5.2	Frame transmissions .....	9
5.3	Bus access method .....	11
5.4	Information routing .....	11
5.5	Network flexibility .....	11
5.6	Remote data request .....	11
5.7	Error detection .....	11
5.8	Error signalling and recovery time .....	11
5.9	Fault confinement .....	12
5.10	Error-active .....	12
5.11	Error-passive .....	12
5.12	Bus-off .....	12
5.13	ACK .....	12
5.14	Repetition of transmission attempts .....	12
5.15	Network-wide data consistency .....	12
5.16	Switchable operating modes of the PMA .....	13
5.17	Bus states and MAC sub-layer phases .....	13
6	CANDLL specification .....	14
6.1	General .....	14
6.2	Time stamping .....	14
6.3	DLL protocol .....	14
6.4	LLC sub-layer .....	15
6.4.1	Overview .....	15
6.4.2	Notifications .....	16
6.4.3	Structure of LLC frames .....	16
6.4.4	Limited LLC frames .....	17
6.4.5	Services of LLC sub-layer .....	17
6.5	Functions of the LLC sub-layer .....	21
6.5.1	General .....	21
6.5.2	Flow control on re-arbitration .....	21
6.5.3	Flow control on retransmission .....	21
6.5.4	Frame acceptance filtering .....	22
6.5.5	Overload notification .....	22
6.5.6	Recovery management .....	22
6.5.7	Time stamping .....	22
6.6	MAC sub-layer .....	23
6.6.1	Functions and rules .....	23
6.6.2	Services of the MAC sub-layer .....	23

6.6.3	Time reference points .....	23
6.6.4	Functional model of MAC sub-layer architecture .....	23
6.6.5	Specification of EF .....	27
6.6.6	Specification of OF .....	28
6.6.7	Inter-frame space specification .....	28
6.6.8	SOF .....	30
6.6.9	Elements of the MAC frame .....	30
6.6.10	MAC frame in CBFF and CEFF .....	31
6.6.11	MAC frame in FBFF and FEFF .....	33
6.6.12	MAC frame in XLFF .....	37
6.6.13	MAC frame coding .....	42
6.6.14	Data frame acknowledgement .....	43
6.6.15	Frame validation .....	43
6.6.16	Order of bit transmission .....	43
6.6.17	Medium access method .....	43
6.6.18	MAC data consistency .....	45
6.6.19	Restricted operation .....	45
6.6.20	Bus monitoring .....	45
6.6.21	Error handling and overload handling .....	45
7	PLspecifications .....	49
7.1	General and functional modelling .....	49
7.2	Services of the PCS interface .....	50
7.2.1	Requirements .....	50
7.2.2	PCS_Data.Request .....	50
7.2.3	PCS_Data.Indicate .....	50
7.2.4	PCS_Mode.Request .....	50
7.2.5	PCS_Status.Transmitter .....	51
7.2.6	PCS_Status.Receiver .....	51
7.3	PCS .....	51
7.3.1	Bit encoding/decoding .....	51
7.3.2	Bit time .....	51
7.3.3	Configuration of the bit time parameters .....	55
7.3.4	Transmitter delay compensation .....	56
7.3.5	Synchronization .....	58
7.3.6	Tolerance range of the oscillator frequencies .....	60
7.4	Attachment unit interface .....	61
7.4.1	General .....	61
7.4.2	PCS to PMA symbols .....	61
7.4.3	PMA to PCS symbol .....	62
7.5	PWM encoding .....	62
7.5.1	General function and definitions .....	62
7.5.2	PCS without PWM encoding .....	63
7.5.3	PCS sub-layer with PWM encoding .....	63
8	Description of supervisor FCE .....	66
8.1	Fault confinement .....	66
8.1.1	Objectives .....	66
8.1.2	Strategies .....	66
8.1.3	Fault confinement interface specification .....	66
8.1.4	Rules of fault confinement .....	69
8.1.5	Node start-up .....	71
8.2	Bus failure management .....	71
Annex A (normative)	CAN FD light -- Data link layer and physical coding sub-layer requirements of responder nodes .....	72
Annex B (informative)	Configuration interface .....	80
Annex C (informative)	Additional information .....	81
Bibliography	.....	82