ISO 23793-1:2024-07 (E)

Intelligent transport systems - Minimal risk manoeuvre (MRM) for automated driving - Part 1: Framework, straight-stop and in-lane stop

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Abbreviated terms 3

5 Function framework 3
5.1 MRM description 3
5.2 State diagram 3
5.2.1 General 3
5.2.2 ADS active (1) 4
5.2.3 Minimal risk condition (4) 5
5.2.4 Sustained standstill management (5) 5
5.2.5 Manual driving (6) 5
5.3 Functionality 5
5.4 Classification 6
5.4.1 Overview 6
5.4.2 Traffic lane stop 6
5.4.3 Road shoulder stop 7
5.4.4 MRM type change 7

6 Requirements 9
6.1 General requirements 9
6.1.1 Overview 9
6.1.2 Vehicle and ADS status monitoring 9
6.1.3 MRM triggering conditions 9
6.1.4 Decision-making for MRM types 9
6.1.5 Operational speed of an MRM 9
6.1.6 Implementation of an MRM 9
6.1.7 Human user takeover of the DDT during an MRM 10
6.1.8 Deceleration control 10
6.1.9 Standstill management 10
6.1.10 Resumption of operation after an MRC 10
6.1.11 Collision mitigation and avoidance function 10
6.1.12 Failure mitigation strategy 10
6.1.13 Internal/external status information 10
6.2 Straight stop requirements 11
6.2.1 Operational speed 11
6.2.2 Detection capability 11
6.2.3 Acceleration control 11
6.2.4 Lateral control 11
6.2.5 MRC location 11
6.3 In-lane stop requirements 11
6.3.1 Operational speed 11
6.3.2 Detection capability 11

6.3.3 Acceleration control 11
6.3.4 Lateral control 11
6.3.5 MRC location 12

7 Performance evaluation test methods 12
7.1 General 12
7.2 Test conditions 12
7.2.1 General 12
7.2.2 Environmental and test course conditions 12

7.2.3 Test vehicle conditions 12
7.3 Test requirements 12
7.3.1 Safety requirements 12
7.3.2 Test case development 13
7.4 Basic MRM function test 13
7.4.1 Test procedure 13
7.4.2 Test confirmation 13
7.5 Human user takeover test 14
7.5.1 Test procedure 14
7.5.2 Test confirmation 14

Bibliography 15