

ISO 23793-1:2024-07 (E)

Intelligent transport systems - Minimal risk manoeuvre (MRM) for automated driving - Part 1: Framework, straight-stop and in-lane stop

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	3
5	Function framework	3
5.1	MRM description	3
5.2	State diagram	3
5.2.1	General	3
5.2.2	ADS active (1)	4
5.2.3	Minimal risk condition (4)	5
5.2.4	Sustained standstill management (5)	5
5.2.5	Manual driving (6)	5
5.3	Functionality	5
5.4	Classification	6
5.4.1	Overview	6
5.4.2	Traffic lane stop	6
5.4.3	Road shoulder stop	7
5.4.4	MRM type change	7
6	Requirements	9
6.1	General requirements	9
6.1.1	Overview	9
6.1.2	Vehicle and ADS status monitoring	9
6.1.3	MRM triggering conditions	9
6.1.4	Decision-making for MRM types	9
6.1.5	Operational speed of an MRM	9
6.1.6	Implementation of an MRM	9
6.1.7	Human user takeover of the DDT during an MRM	10
6.1.8	Deceleration control	10
6.1.9	Standstill management	10
6.1.10	Resumption of operation after an MRC	10
6.1.11	Collision mitigation and avoidance function	10
6.1.12	Failure mitigation strategy	10
6.1.13	Internal/external status information	10
6.2	Straight stop requirements	11
6.2.1	Operational speed	11
6.2.2	Detection capability	11
6.2.3	Acceleration control	11
6.2.4	Lateral control	11
6.2.5	MRC location	11
6.3	In-lane stop requirements	11
6.3.1	Operational speed	11
6.3.2	Detection capability	11

6.3.3	Acceleration control	11
6.3.4	Lateral control	11
6.3.5	MRC location	12
7	Performance evaluation test methods	12
7.1	General	12
7.2	Test conditions	12
7.2.1	General	12
7.2.2	Environmental and test course conditions	12
7.2.3	Test vehicle conditions	12
7.3	Test requirements	12
7.3.1	Safety requirements	12
7.3.2	Test case development	13
7.4	Basic MRM function test	13
7.4.1	Test procedure	13
7.4.2	Test confirmation	13
7.5	Human user takeover test	14
7.5.1	Test procedure	14
7.5.2	Test confirmation	14
	Bibliography	15