

# DIN EN ISO 15118-10:2025-05 (E)

## Road vehicles - Vehicle to grid communication interface - Part 10: Physical layer and data link layer requirements for single-pair Ethernet (ISO 15118-10:2025); English version EN ISO 15118-10:2025

<b>Contents</b>		<b>Page</b>
Foreword.....		iv
Introduction.....		v
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Abbreviated terms</b> .....	<b>2</b>
<b>5</b>	<b>Conventions</b> .....	<b>3</b>
5.1	Definition of OSI based services.....	3
5.2	Requirement structure.....	3
<b>6</b>	<b>System architecture</b> .....	<b>3</b>
6.1	Communication layers.....	3
6.1.1	Architecture.....	3
6.1.2	Layer 2 interfaces.....	4
6.1.3	Communication media.....	4
6.1.4	Data SAP.....	4
6.1.5	Service primitive concept of OSI layered architecture.....	6
6.2	Physical channel.....	6
6.2.1	General.....	6
6.2.2	Nodes.....	7
6.2.3	Requirements for the physical channel.....	7
6.2.4	Schematic of the coupling network.....	7
6.3	System requirements.....	8
6.3.1	Overview of basic signalling.....	8
6.3.2	Electric vehicle supply equipment (EVSE).....	9
6.3.3	Electric vehicle (EV).....	9
<b>7</b>	<b>Connection coordination</b> .....	<b>10</b>
7.1	General.....	10
7.2	Overview.....	10
7.3	Plug-in phase.....	10
7.3.1	General.....	10
7.3.2	EVSE side.....	10
7.3.3	EV side.....	10
7.4	Initialization phase.....	10
7.5	Loss of communication.....	10
7.5.1	General.....	10
7.5.2	EVSE side.....	11
7.5.3	EV side.....	11
7.6	Sleep mode and wake-up.....	11
7.6.1	General.....	11
7.6.2	Entering sleep mode.....	11
7.6.3	Wake-up.....	11
7.7	During a charge pause.....	12
<b>8</b>	<b>Timing and constants</b> .....	<b>12</b>
<b>9</b>	<b>EV-EVSE communication initialization</b> .....	<b>13</b>
9.1	Overview.....	13
9.2	Errors.....	13
<b>10</b>	<b>EMC requirements</b> .....	<b>13</b>
Bibliography.....		14