

# ISO 7856:2025-06 (E)

## Intelligent transport systems - Remote support for low speed automated driving systems (RS-LSADS) - Performance requirements, system requirements and performance test procedures

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b>		<b>v</b>
<b>Introduction</b>		<b>vi</b>
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>1</b>
<b>4</b>	<b>Symbols and abbreviated terms</b>	<b>3</b>
	4.1 Symbols	3
	4.2 Abbreviated terms	3
<b>5</b>	<b>RS-LSADS architecture</b>	<b>4</b>
<b>6</b>	<b>Functions of RS-LSADS</b>	<b>6</b>
	6.1 General	6
	6.2 Remote monitoring	6
	6.3 Remote assistance	6
	6.4 Remote driving	6
<b>7</b>	<b>RS-LSADS functional scenarios</b>	<b>7</b>
	7.1 Remote support scenarios	7
	7.1.1 Scenario 1: Re-starting after stopping at the bus bay	7
	7.1.2 Scenario 2: Entering the unsignalized intersection	8
	7.1.3 Scenario 3: Entering the signalized intersection (signal information only)	9
	7.1.4 Scenario 4: Entering the signalized intersection (signal information and both lateral directions check)	9
	7.1.5 Scenario 5: Bypassing obstacles that block the vehicle path	10
	7.1.6 Scenario 6: Out of ODD due to environmental conditions	11
<b>8</b>	<b>System requirements</b>	<b>12</b>
	8.1 General	12
	8.2 RS-LSADS state transition diagram	12
	8.2.1 State functional descriptions	14
	8.2.2 State transition descriptions	15
<b>9</b>	<b>Communication performance for remote support</b>	<b>16</b>
	9.1 General	16
	9.2 Latency in remote support	17
	9.3 End-to-end information latency	17
	9.4 Information update rate	18
	9.5 Distance error due to latency	18
	9.6 Communication messages for remote support	19
	9.6.1 Vehicle data	19
	9.6.2 LSADS data	20
	9.6.3 Driving environment data	20
	9.6.4 Driving environment audio and video information	20
	9.6.5 Passenger status onboard audio and video information	20
	9.6.6 Remote assistance data	20
	9.6.7 Remote driving control data	20
	9.6.8 Infrastructure sensors data	20
	9.6.9 Infrastructure audio and video information	20

<b>10</b>	<b>RS-LSADS performance requirements</b> .....	<b>21</b>
10.1	Remote monitoring performance.....	21
10.1.1	End-to-end communication requirement during remote assistance standby or remote driving standby.....	21
10.2	Remote assistance performance.....	21
10.2.1	Monitoring data for remote assistant.....	21
10.2.2	Roles of remote assistant.....	21
10.2.3	Remote assistant response to RFI.....	22
10.2.4	Remote assistance HMI, and video field of view and audio.....	23
10.2.5	End-to-end communication requirements during remote assistance.....	23
10.2.6	Data storage requirements for remote assistance.....	23
10.3	Remote driving performance.....	24
10.3.1	Monitoring data for remote driver.....	24
10.3.2	Remote driving response to RFD.....	24
10.3.3	Remote driving HMI, video field of view and audio.....	24
10.3.4	End-to-end communication requirements during remote driving.....	25
10.3.5	Limitations of remote driving.....	25
10.3.6	Alert and warning in remote driving.....	25
10.3.7	Data storage requirements for remote driving.....	25
<b>11</b>	<b>Scenario evaluation test procedures</b> .....	<b>25</b>
11.1	General.....	25
11.2	Test conditions.....	26
11.2.1	Subject vehicle conditions.....	26
11.2.2	Target vehicle or objects conditions.....	26
11.2.3	Environmental conditions.....	26
11.2.4	End-to-end communication setup for scenario tests.....	26
11.3	Test procedures.....	27
11.3.1	General.....	27
11.3.2	Tests for remote assistance.....	27
11.3.3	Tests for Remote driving.....	38
	<b>Annex A (informative) An Example of RS-LSADS Implementation</b> .....	<b>46</b>
	<b>Annex B (informative) An example of the interaction between the control centre and the vehicle for LSADS equipped vehicle mobility service</b> .....	<b>47</b>
	<b>Annex C (informative) Examples of remote support required scenarios and specific operations by RS-LSADS</b> .....	<b>49</b>
	<b>Bibliography</b> .....	<b>57</b>