

ISO/TR 24935:2025-07 (E)

Road vehicles - Software update over the air using mobile cellular network

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviated terms | 2 |
| 5 | General | 3 |
| 5.1 | Purpose | 3 |
| 5.2 | Structure of this document | 4 |
| 5.3 | Reference model | 6 |
| 5.4 | Cybersecurity model | 7 |
| 5.4.1 | General | 7 |
| 5.4.2 | Use of cryptography | 7 |
| 5.4.3 | Cryptographic key management model | 9 |
| 6 | Preparation of the SUP | 11 |
| 6.1 | General | 11 |
| 6.2 | Format of the SUP | 11 |
| 6.2.1 | General | 11 |
| 6.2.2 | Information to resolve the target vehicles and recipients into recipient vehicles | 12 |
| 6.2.3 | Information to resolve the target ECUs into recipient ECUs | 12 |
| 6.2.4 | Vehicle state for successful software update operation | 12 |
| 6.2.5 | Compatibility with the related ECUs in the recipient vehicles | 12 |
| 6.2.6 | Dependency with the related ECUs in the recipient vehicles | 12 |
| 6.2.7 | Interaction with the vehicle user | 13 |
| 6.2.8 | Information for the prerequisite of the installation and the activation during the software update operation | 13 |
| 6.3 | Verification and validation of an SUP | 13 |
| 7 | Operation between infrastructure and vehicles | 13 |
| 7.1 | General | 13 |
| 7.2 | Capabilities and functions in the infrastructure | 14 |
| 7.2.1 | Structure of update server | 14 |
| 7.2.2 | Cybersecurity check | 15 |
| 7.2.3 | Resolving the target vehicles into recipients | 15 |
| 7.2.4 | Failure handling | 16 |
| 7.2.5 | Mobile cellular network | 16 |
| 7.3 | Flow of activities | 16 |
| 7.3.1 | Uploading and storing SUP | 17 |
| 7.3.2 | Resolving target vehicles into recipients | 18 |
| 7.3.3 | Verifying the VCI | 19 |
| 7.3.4 | Transferring SUPs and receiving the results of the software update operation | 20 |
| 7.3.5 | Managing and maintaining of software update campaign | 22 |
| 8 | Software update operation in vehicles | 22 |
| 8.1 | General | 22 |

| | | |
|-------|--|----|
| 8.1.1 | General | 22 |
| 8.1.2 | Overview of EE architecture in vehicle | 23 |
| 8.1.3 | Generic functions of components | 24 |
| 8.2 | Overview of procedures for software update operation | 25 |
| 8.2.1 | General | 25 |
| 8.2.2 | Preparation and receipt of software update operations | 25 |
| 8.2.3 | Installation of software update operation | 26 |
| 8.2.4 | Activation of software update operation | 27 |
| 8.3 | Generic redundant flash bootloader | 28 |
| 8.3.1 | General | 28 |
| 8.3.2 | General operation of the bootloader in an ECU | 28 |
| 8.3.3 | BSBs receipt and installation operations of the bootloader in an ECU | 29 |
| 8.3.4 | Fail recovery operation of the bootloader in an ECU | 31 |
| 8.4 | Communications within the vehicle | 32 |
| 8.4.1 | General | 32 |
| 8.4.2 | Generic Ethernet protocols in vehicle | 32 |
| 8.4.3 | UDSonIP in AVTP for update in vehicle | 32 |
| 9 | Evaluation of overall software update operation | 34 |
| 9.1 | General | 34 |
| 9.2 | Evaluation of software update operation | 35 |
| 9.2.1 | General | 35 |
| 9.2.2 | Evaluation of transmission speed between CM server and ECUs | 35 |
| 9.2.3 | Evaluation of successful transfer | 36 |
| | Annex A (informative) KMIP request/response message | 38 |
| | Bibliography | 44 |