

# ISO 17387:2026-02 (E)

## Intelligent transport systems - Lane change decision aid systems (LCDAS) - Performance requirements and test procedures

---

### Contents

Page

Foreword	v
Introduction	vi
<b>1</b> Scope	<b>1</b>
<b>2</b> Normative references	<b>1</b>
<b>3</b> Terms and definitions	<b>1</b>
<b>4</b> Classification	<b>4</b>
4.1 Coverage zone classification	4
4.1.1 General	4
4.1.2 Type I systems	4
4.1.3 Type II systems	5
4.1.4 Type III systems	5
4.2 Target vehicle closing speed classification	5
4.3 Optional target vehicle closing speed classification for road curvature	6
4.3.1 Overview	6
4.3.2 Type A systems	7
4.3.3 Type B systems	7
4.3.4 Type C systems	8
<b>5</b> Functional requirements	<b>9</b>
5.1 LCDAS state diagram	9
5.1.1 General	9
5.1.2 LCDAS inactive state	9
5.1.3 Activation criteria	9
5.1.4 LCDAS active state	10
5.2 System performance	11
5.2.1 General	11
5.2.2 Minimum detectable target vehicle	12
5.2.3 Requirements for the blind spot warning function	13
5.2.4 Requirements for the closing vehicle warning function	14
5.2.5 Requirements for the lane change warning function	16
5.2.6 System response time	17
5.3 User interface	17
5.3.1 LCDAS status indication	17
5.3.2 LCDAS warning indication	17
5.3.3 LCDAS failure indication	17
5.4 Operation with trailers	18
5.5 Self-test requirements	18
<b>6</b> Test requirements	<b>18</b>
6.1 Test target vehicle	18
6.2 Environmental conditions	18
6.3 Blind spot warning test requirements	18
6.3.1 General	18
6.3.2 Blind spot warning test measurement system	18
6.3.3 Blind spot warning test procedures	19
6.4 Closing vehicle warning test requirements	25
6.4.1 General	25
6.4.2 Closing vehicle warning test measurement system	25
6.4.3 Closing vehicle warning test procedures	26

- 6.5 Lane change warning test requirements .....31
  - 6.5.1 General .....31
  - 6.5.2 Lane change warning test measurement system.....31
  - 6.5.3 Lane change warning test procedures .....32
- Annex A (informative) Blind spot warning example cases..... 37**
- Annex B (informative) Closing vehicle warning test speeds for systems with optional curvature types..... 45**
- Bibliography.....46**