

# ISO 11898-2:2026-05 (E)

## Road vehicles - Controller area network (CAN) - Part 2: High-speed physical medium attachment (PMA) sublayer

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b>		<b>iv</b>
<b>Introduction</b>		<b>v</b>
<b>1 Scope</b>		<b>1</b>
<b>2 Normative references</b>		<b>1</b>
<b>3 Terms and definitions</b>		<b>1</b>
<b>4 Abbreviated terms</b>		<b>3</b>
<b>5 HS-PMA function</b>		<b>4</b>
5.1 Base requirements		4
5.2 HS-PMA test circuit		4
5.3 Static parameter		5
5.3.1 Maximum ratings of $V_{CAN\_H}$ , $V_{CAN\_L}$ and $V_{Diff}$		5
5.3.2 Recessive output characteristics, bus biasing active		5
5.3.3 Recessive output characteristics, bus biasing inactive		6
5.3.4 Dominant output characteristics		6
5.3.5 Maximum driver output current		8
5.3.6 PMA static receiver input characteristics, bus biasing active and inactive		8
5.3.7 Receiver input resistance		9
5.3.8 Maximum leakage currents of CAN_H and CAN_L		10
5.4 Dynamic parameter		10
5.4.1 Driver symmetry		10
5.4.2 Optional transmit dominant timeout		11
5.4.3 Transmitter and receiver timing behaviour		11
5.5 Wake-up from low-power mode		15
5.5.1 Wake-up procedures		15
5.5.2 General requirement		15
5.5.3 Basic wake-up		15
5.5.4 Via wake-up pattern		15
5.5.5 Selective wake-up		19
5.5.6 Bus biasing procedure		24
<b>6 Conformance</b>		<b>26</b>
<b>Annex A (normative) HS-PMA with SIC mode and FAST mode</b>		<b>27</b>
<b>Annex B (informative) ECU and network design</b>		<b>54</b>
<b>Annex C (informative) PN physical layer modes</b>		<b>60</b>
<b>Bibliography</b>		<b>61</b>