ISO 19725:2026-05 (E)

Road vehicles - Steer-by-wire systems - System safety guidelines

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 List of symbols **4**

5 Derivation of the safety goals **4**

5.1 System boundary 4

5.2 SbW malfunctioning behaviours 7

5.3 Safety goals 7

5.3.1 General 7

5.3.2 Safety goal SG1: Self-steering shall be prevented while driving 8

5.3.3 Safety goal SG2: Loss of steerability shall be prevented while driving 9

5.3.4 Safety goal SG3: Loss of feedback torque to the driver shall be prevented while driving 10

5.3.5 Safety goal SG4: Unintentional blocking of the steering wheel shall be prevented while driving 11

5.3.6 Safety goal SG5: Unintended loss of synchronization between the SbW actuators shall be prevented while driving 12

6 System availability requirements **13**

6.1 Availability requirements 13

6.2 Availability requirements after fault 14

6.3 Availability requirements for mechanical system parts 15

7 Controllability in the event of a first fault **15**

7.1 Introduction and general information on controllability 15

7.2 Failure pattern 16

7.2.1 General 16

7.2.2 Malfunction behaviours 16

7.2.3 Failure source 16

7.2.4 Failure type 16

7.2.5 Failure characteristics with the associated physical values 17

7.2.6 Failure pattern with loss of actively generated feedback torque - supplementary instruction 22

7.3 Failure pattern matrix 23

7.4 Assessment of controllability in case of a fault 24

7.4.1 General 24

7.4.2 Failure pattern-driving manoeuvre combinations 25

7.4.3 Controllability thresholds 25

7.4.4 Subjective controllability assessment and related objective vehicle dynamics characteristics 26

7.5 Driving manoeuvres and test execution for the assessment of controllability in the event of a fault 27

8 Minimum requirements for operating behaviour after a fault **27**

8.1 Introduction and general description of the degradation concept 27

8.2 Degradations and transitions 29

8.2.1 Normal operation N 29

8.2.2 Transition x-2 and Degradation 2 29

8.2.3 Transition 2-3 and Degradation 3 30
8.2.4 Transition x-emergency stop 30
8.2.5 Transition N-1 and Degradation 1 30
8.2.6 Transition x-3 30
8.3 General requirements of the degradation concept 31
8.3.1 Controllability during degradations and transitions 31
8.3.2 Electrical power supply system 31
8.3.3 Shortened transitions 31
8.3.4 Performance requirements for the vehicle lateral acceleration 32
8.3.5 Unrestricted continued driving before an automated speed reduction 32
8.3.6 Overriding the automated speed reduction and speed limiter 33
8.3.7 Braking during the automated speed reduction 33
8.4 Differentiation of vehicle systems 33
8.5 Minimum requirements for degradations and transitions 33
8.5.1 General 33
8.5.2 System integrity and speed limitations 34
8.5.3 Requirements for ASIL capability 40
8.5.4 Time-limited usage 41
8.5.5 Re-transitioning and its conditions 43
8.5.6 Requirements for the warning concept 46
8.5.7 Minimum requirements for lateral control and controllability of the vehicle 47
8.6 Manoeuvre sequences and their requirements 48
8.6.1 General explanations 48
8.6.2 Goals of the manoeuvre sequences and associated manoeuvres 48
8.6.3 General requirements 50

Annex A (normative) **Driving manoeuvres for assessment of controllability** **52**

Annex B (normative) **Tests to verify vehicle lateral control and controllability in the degradations and transitions** **62**

Annex C (informative) **Development responsibility** **86**

Annex D (informative) **Experience values from test series during the preparation of the standard** **91**

Annex E (informative) **Explanation of degradation concept** **94**

Bibliography **100**