

ISO 612:1978-03 (E)

Road vehicles; Dimensions of motor vehicles and towed vehicles; Terms and definitions

Contents	Page
1 Scope	1
2 Field of application	1
3 References	1
4 General	1
5 Definition of the longitudinal median plane (of the vehicle)	2
6 Terms and definitions of dimensions of motor vehicles and towed vehicles	3
6.1 Vehicle length	3
6.2 Vehicle width	4
6.3 Vehicle height (unladen)	4
6.4 Wheel space	5
6.5 Track	6
6.6 Front overhang	6
6.7 Rear overhang	6
6.8 Ground clearance	7
6.9 Ramp angle	7
6.10 Approach angle	7
6.11 Departure angle	7
6.12 Height of chassis above ground (commercial vehicles)	8
6.13 Maximum usable length of chassis behind cab (vehicle with cab)	8
6.14 Bodywork length	8
6.15 Maximum internal dimensions of body (commercial vehicles)	9
6.16 Drawgear length	9
6.17 Drawbar length	10
6.18 Position of towing attachment	10
6.19 Fifth wheel lead	11
6.20 Height of coupling face	11
6.21 Distance between towing device and front end of towing vehicle	12
6.22 Rear tractor clearance radius of semi-trailer	12
6.23 Front fitting radius of semi-trailer	12
6.24 Camber angle	12
6.25 Kingpin inclination	13
6.26 Kingpin offset	13
6.27 Toe-in	13
6.28 Castor	14
6.29 Vertical clearance	14
6.30 Lift	14
6.31 Turning lacks	14
6.32 Turning clearance circles	15