

# ISO 612:1978-03 (E)

## Road vehicles; Dimensions of motor vehicles and towed vehicles; Terms and definitions

---

<b>Contents</b>	<b>Page</b>
1 Scope .....	1
2 Field of application .....	1
3 References .....	1
4 General .....	1
5 Definition of the longitudinal median plane (of the vehicle) .....	2
6 Terms and definitions of dimensions of motor vehicles and towed vehicles .....	3
6.1 Vehicle length .....	3
6.2 Vehicle width .....	4
6.3 Vehicle height (unladen) .....	4
6.4 Wheel space .....	5
6.5 Track .....	6
6.6 Front overhang .....	6
6.7 Rear overhang .....	6
6.8 Ground clearance .....	7
6.9 Ramp angle .....	7
6.10 Approach angle .....	7
6.11 Departure angle .....	7
6.12 Height of chassis above ground (commercial vehicles) .....	8
6.13 Maximum usable length of chassis behind cab (vehicle with cab) .....	8
6.14 Bodywork length .....	8
6.15 Maximum internal dimensions of body (commercial vehicles) .....	9
6.16 Drawgear length .....	9
6.17 Drawbar length .....	10
6.18 Position of towing attachment .....	10
6.19 Fifth wheel lead .....	11
6.20 Height of coupling face .....	11
6.21 Distance between towing device and front end of towing vehicle .....	12
6.22 Rear tractor clearance radius of semi-trailer .....	12
6.23 Front fitting radius of semi-trailer .....	12
6.24 Camber angle .....	12
6.25 Kingpin inclination .....	13
6.26 Kingpin offset .....	13
6.27 Toe-in .....	13
6.28 Castor .....	14
6.29 Vertical clearance .....	14
6.30 Lift .....	14
6.31 Turning lacks .....	14
6.32 Turning clearance circles .....	15