ISO 612:1978-03 (E)

Road vehicles; Dimensions of motor vehicles and towed vehicles; Terms and definitions

Contents

Page

1 Scope 1
2 Field of application 1
3 References 1
4 General 1
5 Definition of the longitudinal median plane (of the vehicle) 2
6 Terms and definitions of dimensions of motor vehicles and towed vehicles 3
6.1 Vehicle length 3
6.2 Vehicle width 4
6.3 Vehicle height (unladen) 4
6.4 Wheel space 5
6.5 Track 6
6 6 Front overhang 6
6.7 Rear overhang 6
6.8 Ground clearance 7
6.9 Ramp angle 7
6.10 Approach angle 7
6.11 Departure angle 7
6.12 Height of chassis above ground (commercial vehicles) 8
6.13 Maximum usable length of chassis behind cab (vehicle with cab) 8
6.14 Bodywork length 8
6.15 Maximum internal dimensions of body (commercial vehicles) 9
6.16 Drawgear length 9
6.17 Drawbar length 10
6.18 Position of towing attachment 10
6.19 Fifth wheel lead 11
6.20 Height of coupling face 11
6.21 Distance between towing device and front end of towing vehicle 12
6.22 Rear tractor clearance radius of semi-trailer 12
6.23 Front fitting radius of semi-trailer 12
6.24 Camber angle 12
6.25 Kingpin inclination 13
6.26 Kingpin offset 13
6.27 Toe-in 13
6.28 Castor 14
6.29 Vertical clearance 14
6.30 Lift 14
6.31 Turning lacks 14
6.32 Turning clearance circles 15