

ISO/TR 10305-2:2003-02 (E)

Road vehicles — Calibration of electromagnetic field strength measuring devices —
Part 2: IEEE standard for calibration of electromagnetic field sensors and probes, excluding antennas,
from 9 kHz to 40 GHz

Contents

CLAUSE	PAGE
1. Overview.....	9
1.1 Scope.....	9
1.2 Purpose.....	10
1.3 Background.....	10
1.4 Grades of Calibration.....	10
1.5 Generic Probe Types.....	10
2. References.....	11
3. Definitions.....	12
4. Measurement methods.....	13
4.1 Methods.....	13
4.2 Field sensor or field probe orientation during frequency domain calibration.....	14
4.3 Field probe or field sensor orientation during time domain calibration.....	15
5. Standard field generation methods.....	16
5.1 Frequency domain field generation.....	16
5.2 Time domain field generation.....	17
6. Determining uncertainty.....	17
6.1 Standard uncertainty.....	17
6.2 Combined standard uncertainty.....	17
6.3 Expanded uncertainty.....	18
6.4 Reporting uncertainty.....	18
7. Characteristics to be measured.....	18
7.1 Frequency domain calibration.....	18
7.2 Time domain calibration.....	21
8. Procedures (measurement techniques).....	22
8.1 Transfer standard sensors and probes.....	22
8.2 Transfer and working standard sensors and probes.....	22
8.3 Frequency domain calibration procedure.....	23
8.4 Time domain calibration procedure.....	26
9. Documentation.....	27
9.1 Proper documentation.....	27
9.2 Test documentation.....	27
9.3 Calibration interval.....	28
9.4 Out-of-tolerance notification.....	28
9.5 Certification to customer.....	28

ANNEX	PAGE
Annex A (normative) Grades of calibrations	29
A.1 Grades of calibration.....	29
A.2 Grades of calibration notation summary	32
A.3 Cautions and examples	32
Annex B (normative) methods of field generation and field calculations	34
B.1 Electric and magnetic field generation using a TEM cell, 9 kHz–500 MHz	34
B.2 Magnetic field generation using Helmholtz coils, 9 kHz to 10 MHz	37
B.3 Open-ended waveguide source in anechoic chamber, 200–450 MHz	44
B.4 Pyramidal horn antenna source in an anechoic chamber, 450 MHz–40 GHz	46
B.5 Waveguide chamber, 100 MHz to 2.6 GHz.....	49
B.6 Gigahertz TEM (GTEM) cell, 9 kHz to 1 GHz	50
B.7 Parallel plate transmission line	51
B.8 Conical transmission line.....	53
B.9 Cone and ground plane	53
Annex C (informative) Field sensor and field probe calibration factors.....	55
C.1 Cables.....	56
C.2 Other	57
Annex D (informative) Types of measurements	57
Annex E (informative) Time domain versus frequency domain measurements.....	58
Annex F (informative) Deconvolution	59
Annex G (informative) Burst peak measurement.....	61
Annex H (informative) Examples on determining uncertainty	63
H.1 Standard uncertainty	64
H.2 Combined standard uncertainty	64
H.3 Expanded uncertainty.....	64
H.4 Reporting uncertainty.....	65
Annex I (informative) Time domain pulse fidelity.....	66
Annex J (informative) Bibliography	68