

ISO 6622-2:2003-10 (E)

Internal combustion engines - Piston rings - Part 2: Rectangular rings made of steel

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Overview | 1 |
| 4 | Ring types and designation examples | 1 |
| 4.1 | Type R -- Straight faced rectangular ring | 1 |
| 4.2 | Type B -- Barrel faced rectangular ring | 2 |
| 4.3 | Type BA - Asymmetrical barrel faced rectangular ring h1 W 1,5 mm | 4 |
| 4.4 | Type M -- Taper faced rectangular ring | 5 |
| 5 | Common features | 6 |
| 5.1 | Type R -- Straight faced rectangular ring | 6 |
| 5.2 | Type B -- Barrel faced rectangular ring | 7 |
| 5.3 | Type BA - Asymmetrical barrel faced rectangular ring h1 W 1,5 mm | 8 |
| 5.4 | Type M -- Taper faced rectangular ring | 9 |
| 5.5 | Type R, B, BA and M rings (positive twist type) -- Internal bevel top side | 11 |
| 5.6 | Type M rings (negative twist type), taper M3 to M5 -- Internal bevel bottom side, h1 W 1,5 mm | 11 |
| 5.7 | Type R, B, BA and M rings -- Outside and inside rounded edges | 12 |
| 5.8 | Type R, B, BA and M rings (fully faced and inlaid) -- Plating/coating thickness | 13 |
| 5.9 | Type R, B, BA and M rings -- Nitrided case depth | 13 |
| 6 | Force factors | 14 |
| 7 | Dimensions | 14 |
| Bibliography | | 21 |