

# ISO 4513:2003-10 (E)

## Road vehicles - Visibility - Method for establishment of eyellipses for driver's eye location

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Mathematical description of 3-D eyellipses</b> .....	<b>2</b>
4.1	<b>Axes lengths</b> .....	<b>2</b>
4.2	<b>Centroid</b> .....	<b>3</b>
4.3	<b>Left and right eyes</b> .....	<b>3</b>
4.4	<b>Ellipsoid surface versus three axial sections</b> .....	<b>3</b>
<b>5</b>	<b>Procedure for passenger cars and light trucks</b> .....	<b>3</b>
5.1	<b>3-D eyellipse locating procedure</b> .....	<b>3</b>
<b>6</b>	<b>Procedure for heavy trucks and buses</b> .....	<b>4</b>
6.1	<b>3-D eyellipse locating procedure</b> .....	<b>4</b>
<b>Annex A (informative) Development of the eyellipse</b> .....		<b>6</b>
<b>Annex B (normative) 2-D eyellipse templates</b> .....		<b>8</b>
<b>Bibliography</b> .....		<b>19</b>