

# ISO 4091:2003-11 (E)

## Road vehicles - Connectors for the electrical connection of towing and towed vehicles - Definitions, tests and requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>General requirements .....</b>	<b>3</b>
<b>4.1</b>	<b>Explanations .....</b>	<b>3</b>
<b>4.2</b>	<b>Test sequences .....</b>	<b>3</b>
<b>4.3</b>	<b>Sample requirement .....</b>	<b>4</b>
<b>5</b>	<b>Tests and requirements .....</b>	<b>4</b>
<b>5.1</b>	<b>Visual examination .....</b>	<b>4</b>
<b>5.2</b>	<b>Dimensional check .....</b>	<b>4</b>
<b>5.3</b>	<b>Connection and disconnection .....</b>	<b>5</b>
<b>5.4</b>	<b>Locking device operation .....</b>	<b>5</b>
<b>5.5</b>	<b>Ejector force .....</b>	<b>5</b>
<b>5.6</b>	<b>Locking device and cable retention strength .....</b>	<b>6</b>
<b>5.7</b>	<b>Lateral strength at low temperature .....</b>	<b>6</b>
<b>5.8</b>	<b>Current carrying capacity .....</b>	<b>7</b>
<b>5.9</b>	<b>Connection resistance (voltage drop) .....</b>	<b>8</b>
<b>5.10</b>	<b>Current cycling .....</b>	<b>9</b>
<b>5.11</b>	<b>Withstand voltage .....</b>	<b>9</b>
<b>5.12</b>	<b>Influence of water .....</b>	<b>10</b>
<b>5.13</b>	<b>Static load .....</b>	<b>12</b>
<b>5.14</b>	<b>Protection against dust .....</b>	<b>13</b>
<b>5.15</b>	<b>Endurance .....</b>	<b>13</b>
<b>5.16</b>	<b>Vibration .....</b>	<b>13</b>
<b>5.17</b>	<b>Drop .....</b>	<b>15</b>
<b>5.18</b>	<b>Temperature/humidity cycling .....</b>	<b>16</b>
<b>5.19</b>	<b>Salt spray .....</b>	<b>17</b>
<b>6</b>	<b>Additional required information -- Material specification .....</b>	<b>18</b>