ISO 11898-1:2003-12 (E)

Road vehicles - Controller area network (CAN) - Part 1: Data link layer and physical signalling

Contents

Page

Foreword v

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms and definitions 2

5 Symbols and abbreviated terms 3

6 Basic concepts of CAN 5
6.1 CAN properties 5
6.2 Frames 5
6.3 Bus access method 5
6.4 Information routing 5
6.5 System flexibility 5
6.6 Data consistency 5
6.7 Remote data request 6
6.8 Error detection 6
6.9 Error signalling and recovery time 6
6.10 ACK 6
6.11 Automatic retransmission 6
6.12 Fault confinement 6
6.13 Error-active 6
6.14 Error-passive 6
6.15 Bus-off 7

7 Layered architecture of CAN 7
7.1 Reference to OSI model 7
7.2 Protocol specification 8
7.3 Format description of services 9
7.4 LLC interface 9

8 Description of LLC sublayer 10
8.1 General 10
8.2 Services of LLC sublayer 10
8.3 Functions of LLC sublayer 14
8.4 Structure of LLC frames 14
8.5 Limited LLC frames 16

9 Interface between LLC and MAC 16
9.1 Services 16
9.2 TTC option 16

10 Description of MAC sublayer 17
10.1 General 17
10.2 Services of MAC sublayer 17
10.3 Functional model of MAC sublayer architecture 21
10.4 Structure of MAC frames 24

10.5 Frame coding 29
10.6 Order of bit transmission 30
10.7 Frame validation 30
10.8 Medium access method 30
10.9 Error detection 32
10.10 Error signalling 33
10.11 Overload signalling 33
10.12 Bus monitoring 33

11 LLC and MAC sublayer conformance 33

12 Physical layer 33
12.1 General 33
12.2 Functional model 33
12.3 Services of PL 34
12.4 PLS sublayer specification 35
12.5 PLS-PMA interface specification 39

13 Description of supervisor 39
13.1 Fault confinement 39
13.2 Bus failure management 44

Bibliography 45