

# ISO 11898-2:2003-12 (E)

## Road vehicles - Controller area network (CAN) - Part 2: High-speed medium access unit

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Abbreviated terms</b> .....	<b>3</b>
<b>5</b>	<b>Functional description of MAU</b> .....	<b>3</b>
<b>5.1</b>	<b>General</b> .....	<b>3</b>
<b>5.2</b>	<b>Physical medium attachment sublayer specification</b> .....	<b>3</b>
<b>5.3</b>	<b>MDI specification</b> .....	<b>4</b>
<b>5.4</b>	<b>Physical medium specification</b> .....	<b>4</b>
<b>6</b>	<b>Conformance tests</b> .....	<b>5</b>
<b>6.1</b>	<b>General</b> .....	<b>5</b>
<b>6.2</b>	<b>Recessive output of CAN nodes</b> .....	<b>5</b>
<b>6.3</b>	<b>Dominant output of CAN node</b> .....	<b>6</b>
<b>6.4</b>	<b>Dominant input threshold of CAN node</b> .....	<b>7</b>
<b>6.5</b>	<b>Internal resistance of CAN_L and CAN_H</b> .....	<b>7</b>
<b>6.6</b>	<b>Input capacitances</b> .....	<b>8</b>
<b>6.7</b>	<b>Measurement of the internal delay time</b> .....	<b>10</b>
<b>7</b>	<b>Electrical specification of HS-MAU</b> .....	<b>11</b>
<b>7.1</b>	<b>General</b> .....	<b>11</b>
<b>7.2</b>	<b>Physical medium attachment sublayer specification</b> .....	<b>11</b>
<b>7.3</b>	<b>CAN node</b> .....	<b>14</b>
<b>7.4</b>	<b>MDI specification, connector parameters</b> .....	<b>18</b>
<b>7.5</b>	<b>Physical medium specification</b> .....	<b>18</b>
<b>7.6</b>	<b>Bus failure management</b> .....	<b>19</b>