

# ISO 7308:1987-12 (E)

## Road vehicles; Petroleum-based brake-fluid for stored-energy hydraulic brakes

---

<b>Contents</b>	<b>Page</b>
1 Scope .....	1
2 Field of application .....	1
3 References .....	1
4 Definition .....	1
5 Materials .....	1
6 Requirements.....	1
6.1 Boiling point.....	1
6.2 Viscosity.....	2
6.3 Water content.....	2
6.4 Fluidity and appearance at low temperatures .....	2
6.5 Hygroscopicity.....	2
6.6 Foaming.....	2
6.7 Connpatibility.....	2
6.8 Effect on rubber .....	2
6.9 Performance under simulated Service.....	2
6.10 Corrosion .....	3
6.11 Shear stability.....	3
6.12 Anti-wear stability.....	3
7 Test methods .....	3
7.1 Boiling point.....	3
7.2 Viscosity.....	3
7.3 Water content.....	3
7.4 Fluidity and appearance at low temperatures .....	3
7.5 Hygroscopicity.....	3
7.6 Foaming.....	4
7.7 Compatibility.....	4
7.8 Effect on rubber .....	4
7.9 Performance under simulated Service.....	5
7.10 Corrosion .....	8
7.11 Shear stability.....	10
7.12 Anti-wear properties.....	10
Annexes A Acrylonitrile-butadiene rubber (NBR) brake cups to test brake-fluid complying with ISO 7308.....	11
B Hiding power Chart.....	15
C Mixed formulae and basic mechanical characteristics of the rubber used for tests simulating the effect on rubber .....	16
D Assembly of metal strips for corrosion test in brake-fluids used for full-power hydraulic systems with pump .....	17
E Chemical composition of metal pieces for corrosion test.....	19
F Specifications of balls used in tests carried out with the four-ball machine, for anti-wear properties .....	20