

ISO 10368:2006-02 (E)

Freight thermal containers - Remote condition monitoring

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Performance requirements	3
4.1	General	3
4.2	Requirements	3
4.2.1	System components	3
4.2.2	Performance function	4
4.2.3	Performance constraints	8
5	System compatibility requirements	9
5.1	General	9
5.2	Communications protocol	9
5.2.1	General	9
5.2.2	MMU to MDCU communications	9
5.2.3	MDCU to LRCD communications	33
5.2.4	MDCU to HRCD communications	42
5.3	MMU/Device communications	50
5.3.1	Headers	50
5.3.2	Other MMU/Device messages	50
5.4	Low data rate physical requirements -- LDCU to LRCD	51
5.4.1	Frequency	51
5.4.2	Modulation method	51
5.4.3	Baud rate	51
5.4.4	Transmission mode	51
5.4.5	Injection mode	51
5.4.6	Receiver sensitivity	51
5.4.7	Non-transmission Impedance	51
5.4.8	Bit synchronization	51
5.4.9	Carrier setup time	51
5.4.10	Out-of-band filtering for HDR compatibility	51
5.5	High data rate physical requirements -- HDCU to HRCD	52
5.5.1	Modulation method -- Broad band	52
5.5.2	Transmission mode	52
5.5.3	Injection mode	53
5.5.4	Output/input impedance	53
5.5.5	Power density function	53
5.5.6	Synchronization method	53
5.5.7	Demodulation method	53
5.5.8	Receiver sensitivity	53
5.5.9	Data link protocol	54
5.5.10	Out-of-band filtering requirements for "LDR" compatibility	61
Bibliography		64