

# ISO 10368:2006-02 (E)

## Freight thermal containers - Remote condition monitoring

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Performance requirements .....	3
4.1	General .....	3
4.2	Requirements .....	3
4.2.1	System components .....	3
4.2.2	Performance function .....	4
4.2.3	Performance constraints .....	8
5	System compatibility requirements .....	9
5.1	General .....	9
5.2	Communications protocol .....	9
5.2.1	General .....	9
5.2.2	MMU to MDCU communications .....	9
5.2.3	MDCU to LRCD communications .....	33
5.2.4	MDCU to HRCD communications .....	42
5.3	MMU/Device communications .....	50
5.3.1	Headers .....	50
5.3.2	Other MMU/Device messages .....	50
5.4	Low data rate physical requirements -- LDCU to LRCD .....	51
5.4.1	Frequency .....	51
5.4.2	Modulation method .....	51
5.4.3	Baud rate .....	51
5.4.4	Transmission mode .....	51
5.4.5	Injection mode .....	51
5.4.6	Receiver sensitivity .....	51
5.4.7	Non-transmission Impedance .....	51
5.4.8	Bit synchronization .....	51
5.4.9	Carrier setup time .....	51
5.4.10	Out-of-band filtering for HDR compatibility .....	51
5.5	High data rate physical requirements -- HDCU to HRCD .....	52
5.5.1	Modulation method -- Broad band .....	52
5.5.2	Transmission mode .....	52
5.5.3	Injection mode .....	53
5.5.4	Output/input impedance .....	53
5.5.5	Power density function .....	53
5.5.6	Synchronization method .....	53
5.5.7	Demodulation method .....	53
5.5.8	Receiver sensitivity .....	53
5.5.9	Data link protocol .....	54
5.5.10	Out-of-band filtering requirements for "LDR" compatibility .....	61
Bibliography .....		64