

# DIN EN ISO 12156-1:2008-04 (E)

## Diesel fuel - Assessment of lubricity using the high-frequency reciprocating rig (HFRR) - Part 1: Test method (ISO 12156-1:2006)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	6
4	Principle .....	6
5	Reagents and materials .....	6
6	Apparatus .....	7
7	Preparation and calibration .....	9
7.1	Preparation of apparatus .....	9
7.2	Calibration and correction .....	9
8	Test procedure .....	10
9	Measurement of wear scar .....	11
10	Calculations .....	11
10.1	Uncorrected mean wear scar diameter (MWSD) .....	11
10.2	Initial absolute vapour pressure (AVP1) .....	12
10.3	Final absolute vapour pressure (AVP2) .....	12
10.5	Corrected wear scar diameter (WS <sub>1,4</sub> ) .....	12
11	Test report .....	13
12	Precision .....	13
12.1	Repeatability, r .....	13
12.2	Reproducibility, R .....	13
Annex A (informative) Measurement of HFRR wear scars .....		14
10.4	Mean absolute vapour pressure (AVP) .....	12