

ISO 21214:2006-07 (E)

Intelligent transport systems - Continuous air interface, long and medium range (CALM) - Infra-red systems

Contents		Page
Dedication		iii
Foreword		vii
Introduction		viii
1	Scope	1
2	Conformance	2
3	Normative references	2
4	Terms and definitions	2
4.1	General	2
4.2	Optical parameters	4
5	Symbols and abbreviated terms	8
6	Requirements: transmitter and receiver parameters	10
6.1	Transmitter wavelengths and bandwidths	10
6.2	Radiated power	10
6.2.1	Radiated power limits	10
6.2.2	Transmitter classes	11
6.3	Receiver wavelengths and bandwidths	11
6.4	Receiver class	12
7	Modulation and coding	13
7.1	Generic modulation parameters	13
7.1.1	Wake-up signal	13
7.1.2	Transmitter generic modulation parameters	13
7.1.3	Receiver generic modulation parameters	13
7.2	Communications profiles	13
7.3	Profile 0 (base profile) and profile 1 (default profile) modulation	14
7.4	Profiles 2 to 6	15
8	Directivity and communication zones	16
8.1	Directivity parameters	16
8.2	Communication zones	17
8.2.1	Basic beam	17
8.2.2	Communication zone construction	17
8.2.3	Communication zone shortcuts	18
9	Frames and windows	20
9.1	General structure	20
9.2	Frame	20
9.2.1	Frame structure	20
9.2.2	Frame synchronisation signal (F-Sync)	21
9.3	Windows	21
9.3.1	Window structure and types	21
9.3.2	Window synchronisation (W-Sync)	22
9.3.3	Management window	22

9.3.4	Private window	24
9.3.5	Broadcast window	25
9.3.6	Multicast window	26
9.3.7	Spare window	27
9.3.8	Compatibility window	27
9.3.9	Wake-up window	27
9.4	Command alert (CA)	27
9.5	Summary	29
10	MAC commands	31
10.1	General	31
10.2	MAC commands related to the frame and window organisation	31
10.2.1	frame organisation table (MC-FOT)	31
10.2.2	When generated	32
10.2.3	Effect on receipt	32
10.2.4	frame organisation table update (MC-FOT U)	33
10.2.5	frame organisation table steady (MC-FOT S)	34
10.2.6	Broadcast (MC-BRC)	34
10.2.7	Re-establish session (MC-REST)	35
10.2.8	Session re-establishment confirmed (MC-RESC)	35
10.2.9	Session re-establishment denied (MC-RESD)	36
10.2.10	Kill all (MC-KIA)	36
10.2.11	Kill slave (MC-KIS)	37
10.2.12	De-register (MC-DREG)	37
10.2.13	Suspend all (MC-SUA)	38
10.2.14	Suspend slave (MC-SUS)	39
10.2.15	Free airtime (MC-FAT)	39
10.3	MAC commands related to flow control	40
10.3.1	Command not supported (MC-CNS)	40
10.3.2	Token (MC-TKN)	40
10.3.3	Block start (MC-BLS)	41
10.3.4	Control channel block start (MC-CCBS)	41
10.3.5	IEEE-frame block start (MC-FBS)	42
10.3.6	Start of MAC control block (MC-SMC)	42
10.3.7	Packet start (MC-PAS)	43
10.3.8	Packet end (MC-PAE)	43
10.3.9	Block end (MC-BLE)	44
10.3.10	Transmission acknowledged (MC-TAck)	44
10.3.11	Transmission acknowledged & (MC-TAck&)	45
10.3.12	Transmission not acknowledged (MC-TNAck)	45
10.3.13	Transmission not acknowledged & (MC-TNAck&)	46
10.3.14	Retransmission request (MC-RTQ)	46
10.3.15	Block acknowledge (MC-BAck)	47
10.4	MAC commands related to the registration process	47
10.4.1	Registration enable (MC-REN)	47
10.4.2	Registration request (MC-RRQ)	48
10.4.3	Identifier request (MC-IDQ)	49
10.4.4	Identifier response (MC-IDP)	49
10.4.5	Registration confirmation (MC-REC)	50
10.5	MAC commands related to the physical layer parameters	50
10.5.1	Profiles request (MC-PRQ)	50
10.5.2	Profiles response (MC-PRP)	51
10.5.3	Request new profile (MC-RNP)	52
10.5.4	Set profile (MC-SPR)	52
10.5.5	Set profile confirmation (MC-SPC)	53
10.5.6	Set multicast profile (MC-SMP)	53
10.6	MAC commands related to test and services	54
10.6.1	Status request 1 (MC-SRQ1)	54
10.6.2	Status request 2 (MC-SRQ2)	55
10.6.3	Status request 3 (MC-SRQ3)	56
10.6.4	Status request 4 (MC-SRQ4)	56
10.6.5	Status response 1 (MC-SR1)	57

10.6.6	Status response 2 (MC-SR2)	58
10.6.7	Status response 3 (MC-SR3)	59
10.6.8	Status response 4 (MC-SR4)	60
10.6.9	Echo alert (MC-EA)	61
10.6.10	Echo request (MC-ERQ)	62
10.6.11	Echo (MC-ECH)	62
10.7	MAC command set overview	63
11	Registration procedure	66
11.1	General	66
11.2	Normal registration procedure	66
11.3	Sequence of the registration procedure without collision	67
11.4	Sequence of the registration procedure with collision	67
11.4.1	Both signals appear with equal signal strength	67
11.4.2	Both signals appear with different signal strength	68
11.4.3	Identical TempIDs	68
11.5	Handover and re-registration	68
11.5.1	Cancel TempID	69
11.5.2	Advise adjacent masters	69
11.6	Registration process timers	69
12	Window management	70
12.1	General	70
12.2	Window allocation by frame organisation tables	70
12.3	Spare windows	70
12.4	Windows for isochronous services	71
13	Infra-red management entity	72
13.1	General	72
13.2	MAC command not supported	72
13.3	Communication profiles	72
13.4	Equipment status	72
13.5	Testing	72
13.6	Registration	72
13.7	Session management	73
13.8	Communication	73
13.8.1	Organisation of IR communication	73
13.8.2	Unique block number reference	74
13.9	Window management	74
13.10	MAC tunnel	74
14	Adaptation	75
14.1	Architecture	75
14.2	IR-CAL	75
14.2.1	Communication SAP	75
14.2.2	Communication types	76
14.2.3	WLAN functionality	77
14.2.4	MAC addresses	79
14.2.5	Fragmentation and defragmentation	80
14.3	IR-MAE	80
15	Adoption of other standards and internationally adopted practices	81
16	Marking and labelling	82
17	Declaration of patents and Intellectual Property	83
Annex A (normative) Coding and error correction of profiles 0 and 1 and of commands		86
Annex B (normative) Coding and modulation of profiles 2 to 6		88
Annex C (informative) Link power budget		95

Annex D (informative) Link directivity considerations	101
Annex E (informative) Compatibility of CALM and non-CALM infra-red systems	103
Bibliography	106