

# ISO 4928:2006-07 (E)

Road vehicles - Elastomeric cups and seals for cylinders for hydraulic braking systems using a non-petroleum base hydraulic brake fluid (Service temperature 120 °C max.)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>General requirements .....</b>	<b>2</b>
4.1	Workmanship and finish .....	2
4.2	Marking .....	2
4.3	Packaging .....	2
4.4	Sampling .....	2
<b>5</b>	<b>Test requirements .....</b>	<b>2</b>
5.1	Resistance to fluid at elevated temperature .....	2
5.2	Precipitation .....	2
5.3	Wheel cylinder seals heat pressure stroking .....	2
5.4	Master cylinder seals heat pressure stroking .....	3
5.5	Low-temperature performance .....	4
5.6	Oven ageing .....	4
5.7	Corrosion .....	4
5.8	Storage corrosion test .....	5
<b>6</b>	<b>Test procedures .....</b>	<b>5</b>
6.1	Resistance to fluid at elevated temperature -- Dimensional test .....	5
6.2	Precipitation test .....	7
6.3	Wheel cylinder seals heat pressure stroking .....	8
6.4	Master cylinder seals heat pressure stroking .....	9
6.5	Low-temperature performance .....	11
6.6	Oven ageing .....	12
6.7	Hardness determination .....	12
6.8	Corrosion test .....	13
6.9	Storage corrosion test .....	14