ISO 4928:2006-07 (E)

Road vehicles - Elastomeric cups and seals for cylinders for hydraulic braking s ystems using a non-petroleum base hydraulic brake fluid (Service temperature 120 °C max.)

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 General requirements 2
4.1 Workmanship and finish 2
4.2 Marking 2
4.3 Packaging 2
4.4 Sampling 2

5 Test requirements 2
5.1 Resistance to fluid at elevated temperature 2
5.2 Precipitation 2
5.3 Wheel cylinder seals heat pressure stroking 2
5.4 Master cylinder seals heat pressure stroking 3
5.5 Low-temperature performance 4
5.6 Oven ageing 4
5.7 Corrosion 4
5.8 Storage corrosion test 5

6 Test procedures 5
6.1 Resistance to fluid at elevated temperature -- Dimensional test 5
6.2 Precipitation test 7
6.3 Wheel cylinder seals heat pressure stroking 8
6.4 Master cylinder seals heat pressure stroking 9
6.5 Low-temperature performance 11
6.6 Oven ageing 12
6.7 Hardness determination 12
6.8 Corrosion test 13
6.9 Storage corrosion test 14