

ISO 4928:2006-07 (E)

Road vehicles - Elastomeric cups and seals for cylinders for hydraulic braking systems using a non-petroleum base hydraulic brake fluid (Service temperature 120 °C max.)

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	General requirements	2
4.1	Workmanship and finish	2
4.2	Marking	2
4.3	Packaging	2
4.4	Sampling	2
5	Test requirements	2
5.1	Resistance to fluid at elevated temperature	2
5.2	Precipitation	2
5.3	Wheel cylinder seals heat pressure stroking	2
5.4	Master cylinder seals heat pressure stroking	3
5.5	Low-temperature performance	4
5.6	Oven ageing	4
5.7	Corrosion	4
5.8	Storage corrosion test	5
6	Test procedures	5
6.1	Resistance to fluid at elevated temperature -- Dimensional test	5
6.2	Precipitation test	7
6.3	Wheel cylinder seals heat pressure stroking	8
6.4	Master cylinder seals heat pressure stroking	9
6.5	Low-temperature performance	11
6.6	Oven ageing	12
6.7	Hardness determination	12
6.8	Corrosion test	13
6.9	Storage corrosion test	14