ISO 6119:2006-08 (E)

Road vehicles - Elastomeric seals for hydraulic disc brake cylinders using a non-petroleum base hy draulic brake fluid (Service temperature 120 °C max.)

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Product requirements 1

4 Brake test fluid 1

5 Apparatus 2
5.1 Apparatus for test of resistance to fluid at elevated temperature, physical stability and precipitation characteristics 2
5.2 Apparatus for high-temperature strocking test (see Figure 1) 2
5.3 Apparatus for low-temperature leakage test (see Figure 2) 3

6 Test requirements 3

7 Preparation of test specimens 4

8 Resistance to fluid at elevated temperature -- Physical stability 4
8.1 Test specimens 4
8.2 Test procedure 4

9 Resistance to fluid at elevated temperature -- Precipitation characteristics 5
9.1 Test specimens 5
9.2 Test procedure 5

10 Resistance to elevated temperature in dry air 6
10.1 Test specimens 6
10.2 Test procedure 6

11 Ambient-temperature stroking test 6
11.1 Test specimens 6
11.2 Test procedure 6

12 High-temperature stroking test 7
12.1 Test specimens 7
12.2 Test procedure 7

13 Low-temperature leakage test 8
13.1 Test specimens 8
13.2 Test procedure 8
13.3 Bend test procedure 9

14 Cycling humidity storage corrosion test 9
14.1 Test specimens 9
14.2 Test procedure 9