

ISO 11890-2:2013-03 (E)

Paints and varnishes - Determination of volatile organic compound (VOC) content - Part 2: Gas-chromatographic method

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	2
5	Required supplementary information	2
6	Apparatus	2
6.1	Gas chromatograph	2
6.2	Sample injection system	3
6.3	Oven	3
6.4	Detector	3
6.5	Capillary column	4
6.6	Qualitative-analysis equipment	4
6.7	Injection syringe	4
6.8	Chart recorder	4
6.9	Integrator	4
6.10	Sample vials	4
6.11	Gas filters	4
6.12	Gases	4
7	Reagents	5
7.1	Internal standard	5
7.2	Calibration compounds	5
7.3	Dilution solvent	5
7.4	Marker compound	5
8	Sampling	5
9	Procedure	5
9.1	Density	5
9.2	Water content	6
9.3	Gas-chromatographic conditions	6
9.4	Qualitative analysis of product	6
9.5	Calibration	6
9.6	Sample preparation	7
9.7	Quantitative determination of compound content	7
10	Calculation	8
10.1	General	8
10.2	Method 1: VOC content, as a percentage by mass, of the product "ready for use"	8
10.3	Method 2: VOC content, in grams per litre, of the product "ready for use"	9
10.4	Method 3: VOC content, in grams per litre, of the product "ready for use" less water	9
10.5	Method 4: VOC content, in grams per litre, of the product "ready for use" less water and less exempt compounds (only required if national legislation applies)	10

11	Expression of results	10
12	Precision	10
12.1	General	10
12.2	Repeatability limit r	10
12.3	Reproducibility limit R	11
13	Test report	11
	Annex A (normative) Required supplementary information	12
	Annex B (informative) Examples of gas-chromatographic conditions	13
	Bibliography	17